

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER REFS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	FZHX/0156			X
BB	General Purpose "U" bolt clamp	UC3104GP			
CC	Lightening arrester, 10 KV				
DD	Single phase oil switch, 14.4 KV			MG204-1204 KMG2	
EE	split bolt connector, size req'd			BLACK BURN R SHIES	
FF	grounding spec. see det. No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend preforms for ACSR, size req'd				
II	30' class 6 creosoted pine pole				
JJ	OVERHEAD GRND, 44 ACSR - If Req'd - Ref. Det. ES-11.				
KK	ES-1A - Note 3				
LL	ground connector, motor			BLANDY KC.22	X
MM	600 V. secondary lightning arrester single phase				
NN	Greenfield Type KF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
OO	req'd size LB fitting & cover & gasket				
PP	transformer tank grounding terminal	GWS-15			

CONOCO
PEARL B NO. 5

DATE: 12-27-71	TITLE: DESCRIPTION MATERIAL	
DRAWN BY: E. WINTER	CONOCO HOBBS DIVISION	
DESIGN BY:		
CHECKED BY:		
APPROVED BY:		
SCALE: NONE	JOB: REC SPECS	DRAWING NO.: ES-1 SHEET 2 OF 3

RECEIVED

MAY 17 1977

**OIL CONSERVATION COMM.
HOBBS, N. M.**