

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO. SUB.
a	double upset bolt s/aq. nut, round washer, and cotter key on short end, sq. nut and HF locknut on long end, 15 1/8" long (or length required), wet process porcelain secondary spool insulator, 3", brown glaze	7828			
b	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-18. Note: provide clamp and ground conduit parallel groove clamp, size req'd		1101		
d	secondary insulator clevis for 4" insulator	6510			
e	5/8" thimble nut	5512			
f	5/8" x 12" (or length req'd) straight thimble bolt w/aq. nut				
g	transformer cluster mount bracket (small)			ALUMA FORM 6M3-6	X
h	transformer cluster mount bracket (large)			ALUMA FORM 15M3-6	X
i	req'd size raintight disconnect & fuses, 3-phase, 600 V. Ref. Dwg No. ES-18				
n	16" cross plate anchor (or size req'd)	X-16			
q	8-way expanding anchor (size req'd)	88135			
c	4" brown glaze wet process porcelain secondary spool insulator		10101		
u	3/8" x 7' thimble anchor rod w/nut (use twineye 1/2 req'd - Chance No. 5347)	5317 (w/ 55006P)			
aa	3/8" high strength guy strand (10,800 lb.)				
bb	preformed guy grip for 3/8" guy strand	5010			
dd	5/8" x 10" angle thimble bolt w/nut	68-3 1/2			X
ee	3"x3"x1/4"x11/16" hole curved washer				
ff	6" - guy clamp w/3-1/2" bolts				
gg	medium size strain insulator	6454			
hh	serving sleeve for 3/8" guy strand	7887			X
jj	3/16" x 2-1/2" x 7" lift plate				
mn	pole bottom ground plate (may use butt-wrapp if desired)				
qq	Ground Connection (See Dwg. ES-12)				
rr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

DATE: 12-27-71		TITLE: DESCRIPTION MATERIALS	
DRAWN BY: E. WINTER		CONOCO HOBBS DIVISION	
DESIGN BY:			
CHECKED BY:			
APPROVED BY:			
SCALE: NONE		JOB: ELEC SPECS	DRAWING NO: ES-1
		SHEET 3 OF 5	

CONOCO
PEARL B NO 5

RECEIVED

MAY 17 1977.

OIL CONSERVATION COMM.
HOBBS, N. M.