This form is to be filed with the appropriate District Office of [illegible] commenced not later than [illegible] days after the completion of any newly drilled or deepened well. It shall be accompanied by one copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, zones shall be reported in the order in which they are to be filled. For multiple completions, [illegible] through [illegible] shall be reported for each zone. [illegible] to be filed for [illegible] completion or [illegible] Land, where such [illegible] are required. See Rule 105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy	1554	T. Canyon	11,360	T. Ojo Alamo		T. Penn. "B"	
T. Salt	1664	T. Strawn	11,705	T. Kirtland-Fruitland		T. Penn. "C"	
B. Salt	2604	T. Atoka	11,826	T. Pictured Cliffs		T. Penn. "D"	
T. Yates	2785	T. Miss	13,102	T. Cliff House		T. Leadville	
T. 7 Rivers		T. Devonian	13,832	T. Menefee		T. Madison	
T. Queen	3790	T. Silurian		T. Point Lookout		T. Elbert	
T. Grayburg	4116	T. Montoya		T. Mancos		T. McCracken	
T. San Andres	4404	T. Simpson		T. Gallup		T. Ignacio Qtzte	
T. Glorieta	4945	T. McKee		Base Greenhorn		T. Granite	
T. Paddock		T. Ellenburger		T. Dakota		T.	
T. Blinebry		T. Gr. Wash		T. Morrison		T.	
T. Tubb	7160	T. Granite		T. Todilto		T.	
T. Drinkard	7265	T. Delaware Sand		T. Entrada		T.	
T. Abo	7815	T. Bone Springs		T. Wingate		T.	
T. Wolfcamp	9495	T. Morrow Sd	12,536	T. Chinle		T.	
T. Penn.		T. Chester Lime	12,676	T. Permian		T.	
T. Cisco (Bough C)	10,400	T. Woodford	13,728	T. Penn. "A"		T.	

OIL OR GAS SANDS OR ZONES

No. 1, from 13,988 to 14,012 (Devonian) No. 4, from 10,008 to 10,022 (Wolfcamp)

No. 2, from 12,536 to 12,592 (Morrow) No. 5, from ..... to .....

No. 3, from 9,964 to 9,976 (Wolfcamp) No. 6, from ..... to .....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to ..... feet. .....

No. 2, from ..... to ..... feet. .....

No. 3, from ..... to ..... feet. .....

No. 4, from ..... to ..... feet. .....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
Surface	1,554	1,554	surface rock & redbeds	12,676	13,728	52	lime
1,554	1,664	110	anhydrite & redbeds	13,728	13,832	104	shale
1,664	2,604	940	salt	13,832	11,144	312	Devonian lime & dolomite
2,604	2,785	181	anhydrite, salt, redbeds				
2,785	4,116	1,331	sand, anhydrite, shale				
4,116	4,404	288	dolomite, anhydrite, sand				
4,404	7,160	2,756	dolomite				
7,160	7,265	105	sand				
7,265	7,815	550	dolomite				
7,815	7,858	43	shale, dolomite				
7,858	9,495	1,637	dolomite, shale				
9,495	10,665	1,170	lime, shale				
10,665	10,955	290	shale & shaley lime				
10,955	11,005	50	lime				
11,005	11,360	355	shale				
11,360	12,303	943	lime w/shale stringers				
12,303	12,676	373	sand & shale stringers				

RECEIVED

FEB 9 1978

OIL CONSERVATION COMM.
HOBBS, N. M.