

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	3002525565
5. Indicate Type of Lease	STATE ☐ FEE ☒
6. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
Conoco Inc.

3. Address of Operator
10 Desta Dr, Ste 100W, Midland, Tx 79705

4. Well Location
Unit Letter D : 660 Feet From The West Line and 510 Feet From The North Line

Section 18 Township 16S Range 36E NMPM Lea County
10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3954 GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- It is proposed to plug & abandon the Houston No. 1 well as follows:
1. Set CIBP @ 11314'. Spot 25 sx cmt on top of CIBP @ 11064-11314'. Displace tbq w/66 bbls 10 ppg mud.
 2. Set CIBP @ 10258'. Spot 25 sx cmt on top of CIBP @ 10008-10258'. Displace w/60 bbls 10 ppg mud.
 3. Spot 25 sx cmt from 7258-7508'. Displace tbq w/43 bbls 10 ppg mud.
 4. Spot 25 sx cmt from 6150-6400'. Displace tbq w/37 bbls 10 ppg mud. Pump 15 bbls 10 ppg mud thru csg valve to load hole.
 5. Perf 5-1/2" csg @ 4215'.
 6. Spot 54 sx cmt (9 sx excess) @ 4065-4215' to fill csg annulus & 5-1/2" csg. Pump 10 bbls of 10 ppg mud thru csg valve to load hole.
 7. Perf 5-1/2" csg @ 2028'.
 8. Perf 5-1/2" prod csg & 9-5/8" inter csg @ 405'.
 9. Spot 54 sx cmt (9 sx excess) @ 1878-2028' to fill csg annulus & 5-1/2" csg.
 10. Establish circ. Pump 273 sx cmt (45 sx excess) surf plug in 5-1/2" csg.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Hoover TITLE Sr. Conservation Coordinator DATE 04-06-02
TYPE OR PRINT NAME Jerry W. Hoover (915) 686-6548 TELEPHONE NO.

(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

THIS DOCUMENT MUST BE FILED IN DATE
10-1-89 TO THE RECORDING OF
ELECTRIC OPERATIONS FOR THE C-103
TO BE APPROVED.

APR 09 '92

100-1002
100-1002