

NO. OF COPIES RECEIVED		
DISTRIBUTION		
ANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL <input type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- Dry Hole
1. Name of Operator Rex Alcorn		
2. Address of Operator Ingram Bldg., 100 South Kentucky, Roswell, NM 88201		
3. Location of Well UNIT LETTER K 2310 FEET FROM THE South LINE AND 1980 FEET FROM T-E West LINE, SECTION 35 TOWNSHIP 16 S RANGE 37 E NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name Shipp
9. Well No. 1
10. Field and Pool, or Wildcat West Knowles-Drinkard
12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pits broke out, allowed to dry : Dry hole marker in place : Location leveled
and restored to initial state : Location ready for inspection.

P & A as follows in accordance with instructions of NMOCC:

100 feet (40 sx) from TD to 8438'.
100 feet (40 sx) from 6525' to 6425' (Glorieta).
100 feet (40 sx) from 4250' to 4150' (Bottom 8 5/8" Csg.).
100 feet (30 sx) from 2210' to 2110' (Inside 8 5/8" csg at Top Salt).
10 sx at surface with dry hole marker.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Rex Alcorn</u>	TITLE <u>Operator</u>	DATE <u>7-14-78</u>
APPROVED BY <u>Eddie W. Seay</u>	TITLE <u>OIL & GAS INSPECTOR</u>	DATE <u>NOV 26 1979</u>
CONDITIONS OF APPROVAL, IF ANY:		