

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electric log and radioactivity log run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of diphenomally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 1 through 34 shall be reported for each zone. This form is to be filed in quadruplicate except on state land, where six copies are required. See rule 11.5.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy <u>Rustler 1509'</u>	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt <u>Salado 1684'</u>	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Anoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates <u>2807'</u>	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen <u>3815'</u>	T. Siberian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg <u>4305'</u>	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres <u>4600'</u>	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzite _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Padlock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drunkard _____	T. Delaware Sand _____	T. Entrada _____	T. _____
T. Abo _____	T. Bone Springs _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn. _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from <u>4305'</u> to <u>4700'</u>	No. 4, from _____ to _____
No. 2, from _____ to _____	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from <u>none</u> to _____ feet.
No. 2, from _____ to _____ feet.
No. 3, from _____ to _____ feet.
No. 4, from _____ to _____ feet.

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	416'	416	Sand and redbeds				
416	1216'	800	Redbeds				
1216	1578'	362	Sand and Anhydrite				
1578	2863'	1285	Anhydrite and salt				
2863	3560'	703	Anhydrite				
3560	4116'	556	Lime and dolomite				
4116	4700'	584	Lime				
				REMARKS			
				32. cont....			
				4565-4660' - 8000 gal ref oil, 1# 20/40 sand/gal;			
				12,000 gal ref oil, 1½# 20/4 sand/gal; 4000 gal ref oil,			
				55 gal Sureflo 344; 3000 gal			
				ref oil, 20 ball sealers in			
				1st 500 gal of ea. 1000 gal.			
				Flsh w/ 75 B0, overflsh w/			
				20 B0.			