

GL @ 4122'

12-1/4" hole
8-5/8" O.D., 24#/ft., @ 355'
350 sx., cement circulated

Rustler @ 1503' (+2630')

Yates @ 2806' (+1327')

Queen @ 3801' (+332')

2-3/8" O.D., 4.7#/ft., J-55, EUE
tubing, plastic lined

Baker AD-1 tension packer @ 4100'

Perforations (2 JSPF)

Grayburg @ 4212' (-79')

0 4197'-4203'
0 4345'-4352'
0 4396'-4402'
0 4431'-4433'
0 4436'-4442'
0 4464'-4466'
0 4488'-4494'
0 4503'-4505'
0 4518'-4520'
0 4533'-4537'
0 4539'-4542'
0 4550'-4560'
0 4563'-4587'
0 4640'-4645'

San Andres @ 4589' (-456')

PTD 4757'

X X X X X
X X X X
X X X X X

TD 4800'

7-7/8" hole
4-1/2" O.D., 11.6#/ft., @ 4800'
1750 sx., cement circulated

NO.		REVISION		BY	DATE	CHKD	APP'D	
FOR BIDS		 PHILLIPS PETROLEUM COMPANY BARTLESVILLE, OKLAHOMA				JA NO.		FILE CODE
FOR APPR						AFE NO.		SCALE
FOR CONST		LEAMEX WELL NO. 33 Unit letter H, 1980' FNL, 660' FEL, Sec. 24, T-17-S, R-33-E, Lea Co., N.M.				DWG NO.		
DRAWN						SH NO.		
CHECKED								
APP'D								