

GL @ 4124'

12-1/4" hole
8-5/8" O.D., 24#/ft, @ 425'
400 sx, cement circulated

Rustler @ 1476' (+2659')

Yates @ 2824' (+1311')

Queen @ 3793' (+342')

Grayburg @ 4238' (-103')

2-3/8", 4.7#/ft, J-55, EUE
tubing, plastic lined

Baker AD-1 tension packer @ 4300'

Perforations (2 JSPF)

4390'-4395'
4428'-4435'
4481'-4486'
4508'-4513'
4524'-4529'
4554'-4558'
4561'-4564'

San Andres @ 4570' (-435')

PTD 4644'

TD 4700'

X X X X X
X X X X X
X X X X X

7-7/8" hole
4-1/2" O.D., 11.6#/ft, @ 4700'
1650 sx., cement circulated

NO.		Proposed Completion for Water Injection		BY	DATE	CHKD	APP'D
FOR BIDS		REVISION					
FOR APPR		PHILLIPS PETROLEUM COMPANY		JA NO. FILE CODE			
FOR CONST		BARTLESVILLE, OKLAHOMA		AFE NO. SCALE			
DRAWN		LEAMEX WELL NO. 19 Unit letter D, 1980' FSL, 660' FWL, Sec. 24, T-17-S, R-33-E, Lea Co., N.M.		DWG NO.			
CHECKED				SH NO.			
APP'D							

RECEIVED

OCT - 4 1984

U.S. DEPT. OF JUSTICE
HOUSING OFFICE