

WELL NO.	U S T R	TD (PBD)	TYPE	HOLE SIZE	CASING SIZE	DEPTH	CEMENT	TOC	REMARKS
ILLIPS'E' STATE #29	P 14 175 33E	4800'	OIL	12-1/4"	8-5/8"	440'	400sx	CIRC	
		(4768')		7-7/8"	4-1/2"	4798'	850sx	CIRC	G/SA PERFORATIONS 4429'-4540'
ILLIPS'E' STATE #30	L 13 175 33E	4705'	OIL	12-1/4"	8-5/8"	399'	400sx	CIRC	PROPOSED INJECTION WELL
		(4689')		7-7/8"	4-1/2"	4705'	950sx	CIRC	G/SA PERFORATIONS 4432'-4582'
ILLIPS'E' STATE #32	N 13 175 33E	4707'	OIL	12-1/4"	8-5/8"	416'	550sx	CIRC	
		(4706')		7-7/8"	4-1/2"	4705'	850sx	CIRC	G/SA PERFORATIONS 4465'-4660'
EAMEX #8	B 23 175 33E	11337	PA	17-1/2"	13-3/8"	424'	450sx	CIRC	CUT 5-1/2" CSG AT 3634'
		(11310)		12-1/4"	8-5/8"	4679'	1130sx	50'	400 sx PLUG 3628'-9850';
				8-3/4"	5-1/2"	11336'	325 sx	9375'	10 sx PLUG SURFACE
EAMEX #20	B 23 175 33E	4704'	GAS	12-1/4"	8-5/8"	410'	600sx	CIRC	QUEEN PERFORATIONS 3778'-3801'
		(4661')		7-7/8"	4-1/2"	4704'	1700sx	CIRC	RBP SET AT 4247' TO ISOLATE
									G/SA PERFORATIONS 4388'-4498'
EAMEX #22	H 23 175 33E	4700'	OIL	12-1/4"	8-5/8"	403'	400sx	CIRC	
		(4603')		7-7/8"	4-1/2"	4700'	2150sx	CIRC	G/SA PERFORATIONS 4383'-4561'
EAMEX #23	F 24 175 33E	4700'	OIL	12-1/4"	8-5/8"	410'	600sx	CIRC	
		(4643')		7-7/8"	4-1/2"	4700'	1700sx	CIRC	G/SA PERFORATIONS 4408'-4550'
EAMEX #27	B 24 175 33E	4700'	OIL	12-1/4"	8-5/8"	400'	400sx	CIRC	
		(4660')		7-7/8"	4-1/2"	4700'	1600sx	CIRC	G/SA PERFORATIONS 4424'-4582'
EAMEX #29	L 24 175 33E	4710'	OIL	12-1/4"	8-5/8"	400'	400sx	CIRC	PROPOSED INJECTION WELL
		(4662')		7-7/8"	4-1/2"	4708'	1600sx	CIRC	G/SA PERFORATIONS 4373'-4558'