

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐
Name of Operator
Harvey E. Yates Company
Address of Operator
P. O. Box 1933, Roswell, N.M. 88201
Location of Well
UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM
THE East LINE, SECTION 28 TOWNSHIP 16S RANGE 37E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Burton
9. Well No.
1
10. Field and Pool, or Wildcat
Und. Casey Strawn
12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3786.3' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WELL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <u>Run intermediate casing</u> <input checked="" type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-9-79 Ran 103 joints (4306') 8 5/8"OD, 24# (2366.23'), 28# (1225.90') and 32# (713.87'), new FWP 8R ST&C casing and set at 4323.0' RTM. Cemented with 1430 Sx HLW w/15# Salt/Sx, 3# Gilsomite and 1/4# Flocele/Sx and 200 Sx Cl C - 2% CaCl. Plug down at 9:45 AM. Circulated 120 Sx cement.
5-10-79 WOC 22 1/2 Hours.
5-10-79 Pressured up on 8 5/8" casing with 1500 psi for 30 minutes. OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Engineer DATE 5-21-79

APPROVED BY Jerry Sexton TITLE Dist 1, Supv. DATE MAY 28 1979
CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY 25 1979

**OIL CONSERVATION COMM.
HOBBES, N. M.**