

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED NEW MEXICO OIL CONSERVATION COMMISSION

AUG 17 1979

O. C. C.
ARTEBIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. LC 4534
7. Unit Agreement Name
8. Farm or Lease Name BASS STATE "36"
9. Well No. 1
10. Field and Pool, or Wildcat WILDCAT
12. County EDDY

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
BASS ENTERPRISES PRODUCTION CO.

3. Address of Operator
Box 2760, MIDLAND, TX 79702

4. Location of Well
UNIT LETTER E 660 FEET FROM THE WEST LINE AND 1980 FEET FROM THE NORTH LINE, SECTION 1536 TOWNSHIP 15S RANGE 34E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
4048.3' GL 4067' KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> 8 5/8" INTERMEDIATE CASING

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

DRILLED 11" HOLE TO 4650'.

RAN 113 JTS 8 5/8", 24+32#, K-SS, ST+C CASING. SET AT 4650'.

DV TOOL AT 1901'. FIRST STAGE CEMENT: 1000 SKS "LITE" PLUS ADDITIVES, TAILED WITH 200 SKS CLASS "C". PLUG DOWN @ 11:40 AM, 8/8/79. OPENED DV TOOL AND CIRCULATED OUT 125 SKS. SECOND STAGE CEMENT: 800 SKS "LITE" PLUS ADDITIVES. FULL RETURNS - CEMENT DID NOT CIRCULATE. TOC BY TEMPERATURE SURVEY @ 328' - 11 3/4" SET @ 351'. RAN 3/4" TO 378' IN 11 3/4" - 8 5/8" ANNULUS - PUMPED 100 CLASS "C" PLUS ADDITIVES. CIRCULATED OUT 15 SKS. WOC 12 HOURS. DRILLED DV TOOL - TESTED CASING TO 2000# - HELD OK. DRILLED 5' NEW HOLE - TESTED BACK SIDE TO 500#. DRILLING 7 7/8" HOLE.

Min WOC 18 HRS

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED V. P. Hurty Jr. TITLE Asst. Prod. Clerk DATE Aug. 16, 1979

Orig. Signed by

APPROVED BY Jerry Sexton

CONDITIONS OF APPROVAL, IF ANY Dist 1, Supv.

TITLE

AUG 20 1979