

	O. D.	I. D.	LENGTH	DEPTH
Drill Pipe or Tubing	6 3/8"	3"	1'	
Reversing Sub				
Water Cushion Valve				
Drill Pipe	4 1/2"	3.826"	9802.60'	
Drill Collars	6 1/2"	2 1/2"	750.40'	
Handling Sub & Choke Assembly	6 3/8"	3"	1' X OVER	
Dual CIP Valve				
Dual CIP Sampler	5"	.75"	7'	10555'
Hydro-Spring Tester	5"	.75"	4'	10557'
Multiple CIP Sampler				
Extension Joint				
AP Running Case	5"	3.25"	5'	10566'
Hydraulic Jar	5"	1.75"	5'	
VR Safety Joint	5"	1"	3'	
Pressure Equalizing Crossover				
Packer Assembly	6 3/4"	1.53"	6'	10578'
Distributor	5"	1.68"	2'	
Packer Assembly	6 3/4"	1.53"	6'	10586'
Flush Joint Anchor				
Pressure Equalizing Tube				
Blanked-Off B.T. Running Case				
Drill Collars				
Anchor Pipe Safety Joint				
Packer Assembly				
Distributor				
Packer Assembly				
Anchor Pipe Safety Joint	5.75"	1.5"	4'	
X OVER	6 1/2"	2 1/2"	.80'	
Side Wall Anchor				
Drill Collars	6 1/2"	2 1/2"	63.57'	
X OVER	6 1/2"	3"	1'	
Flush Joint Anchor	5.75"	3.50"	28.90'	
Blanked-Off B.T. Running Case	5.75"	3.50"	6'	10687'
Total Depth				10691'

RECEIVED

JUN 22 1979

**OIL CONSERVATION COMM.
HOBBBS, N. M.**