

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NE MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-1126-5	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Tenneco Oil Company		State 25
3. Address of Operator		9. Well No.
6800 Park Ten Blvd., Suite 200 No. San Antonio, Texas 78213		#101
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>D</u> <u>990</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM		Undesignated
THE <u>West</u> LINE, SECTION <u>25</u> TOWNSHIP <u>16S</u> RANGE <u>33E</u> NMPM.		
11. Elevation (Show whether DF, RT, GR, etc.)		12. County
4162' GR		Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8/12/79 - RAN 103 JTS 8 5/8" 32# K55 8RST&C TO 4627' W 255 SXS "C" JUNK SLURRY; 1300 SXS "C" + 2% A-2 + 5# SALT/SX + 1/4#/SX CELLOFLARE, 200 SXS "C" Heat + 2% CaCl₂ HAD FULL CIRCULATION AT ALL TIMES. BUT NO CEMENT RETURNS, RAN 1" to 180' ON BACK SIDE - CEMENTED THRU 1" W/150 SX "C" + 2% CaCl - CEMENT STAYED UP AFTER 1" JOB - TESTED CASING TO 2000 PSI.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED F.R. Bell TITLE Staff Production Analyst DATE 9-7-79

APPROVED BY Orig. Signed Jerry Sexton TITLE Dist 1, Supv DATE SEP 14 1979

CONDITIONS OF APPROVAL, IF ANY: