

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
J. M. Huber Corporation
3. ADDRESS OF OPERATOR
1900 Wilco Building, Midland, TX 79701
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 700' FSL & 1980' FEL
AT TOP PROD. INTERVAL: 700' FSL & 1980' FEL
AT TOTAL DEPTH: 700' FSL & 1980' FEL
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐

(other) Set 5 1/2" intermediate casing

5. LEASE
NM015072
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Stoliz Federal
9. WELL NO.
2
10. FIELD OR WELDCAT NAME
Morton Wolfcamp
11. SEC. T., R., M., OR B.K. AND SURVEY OR AREA
Sec. 12, T-15S, R-34E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW OF, KDB, AND WD)
4054.6 GR.

RECEIVED

AUG 30 1979

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/25/79 Ran 249 jts. 17# & 15.5# 5 1/2" csg. and set at 10,430' with D.V. tool at 7972'. Cemented 1st stage 5 1/2" csg. - pumped 550 sks. Light cmt. containing 6% Halad 22A, 5# KCL, 1/2# Flo Seal, 3# Gilsonite mixed @ 12.7 ppg tailed in w/250 sks. Class "H" containing .6% Halad 22A, 5# KCL mixed @ 16.4 ppg.

8/26/79 Cemented 2nd stage 5 1/2" csg. - pumped 900 sks. Light cmt. containing 1/2# Flocele, 5# Gilsonite mixed @ 12.7 ppg tailed in w/150 sks. Class "H" neat mixed @ 16.4 ppg. Cmt. top by survey is 5660'.

8/27/79 WOC 24 hours. Move off rig.

Subsurface Safety Valve: Manu. and Type

Set @ Ft

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert G. Setzler
Robert G. Setzler

TITLE Dist. Prod. Mgr

DATE August 29, 1979

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

