

COUNTY LEA FIELD Maljamar STATE NM
OPR ARCO OIL & GAS CO. API 30-025-26552
NO 13 LEASE Johns "B" DE MAP
Sec 24, T17S, R32E CO-ORD
1360' FSL, 2465' FEL of Sec 5-1-16 NM
4 mi SE/Maljamar SPD 12-17-79 CMP 3-28-80

CSC			
8 5/8" at 409' w/175 sx			
4 1/2" at 4300' w/2073 sx			
2 3/8" at 4021'			
WELL CLASS: INT D FIN DO ELEV			
FORMATION	DATUM	FORMATION	DATUM
TD	4300' (SADR)	PBD	4289'

IP (Grayburg-San Andres) Perfs 4167-4275' F 23 BOPD +
2 BW. Pot based on 24 hr test thru 48/64" chk. GOR 391;
gty 36.2; CP 35#; TP 50#

CONTR Cactus #52 OPRSELEV 4050' GL PD 4300' RT

F.R. 11-19-79
(Grayburg-San Andres)
1-2-80 TD 4300'; MORT
1-11-80 TD 4300'; SI
1-18-80 TD 4300'; Tstg Csg
1-24-80 TD 4300'; PBD 4289'; Prep Acid
Perf (San Andres) @ 4267', 4270', 4272', 4275'
w/1 SPI
1-30-80 TD 4300'; PBD 4289'; SI
2-13-80 TD 4300'; PBD 4289'; Plg Tbg
Csg collapsed 4114-24'
Sqzd Csg w/300 sx & DOC
Csg collapsed 4063-75'
Sqzd Csg w/200 sx
2-20-80 TD 4300'; PBD 4289'; Tstg Csg
2-27-80 TD 4300'; PBD 4289'; Tstg Csg
5-1-16 NM

LEA
ARCO OIL & GAS CO.

Maljamar
13 Johns "B" DE
Sec 24, T17S, R32E

NM
Page 2

3-7-80 TD 4300'; PBD 4289'; SI
3-14-80 TD 4300'; PBD 4289'; CO
3-21-80 TD 4300'; PBD 4289'; Swbg
Perf (Grayburg-San Andres) @ 4167', 4173',
4176', 4177', 4178', 4179', 4188', 4189', 4190',
4191' w/1 SPI
Acid (4167-4275') 10,584 gals (15% NE)
Swbd 5 BO + 27 BW in 9 hrs (4167-4275')
3-26-80 TD 4300'; PBD 4289'; SI/WO Prod Equip
4-2-80 TD 4300'; PBD 4289'; WOSP
Flwd 23 BO + 2 BW in 24 hrs thru 48/64"
chk (4167-4275')
4-28-80 TD 4300'; PBD 4289'; Complete
5-1-16 NM

4-28-80 Continued
LOG TOPS: Rustler Anhydrite 1073',
Salt 1210', Base Salt 2552', Grayburg
3570', San Andres 4010'
Rig Released 1-1-80
5-3-80 COMPLETION ISSUED

5-1-16 NM
IC 30-025=70458-79