Shared Josefee Dyna Core Enc.,, Minerals and Namral Resources Department Interds 1:499 Different Diff	+-	State of New Me	rico	
P.O. Box 2088 30-025-26591 SINTECT.T. Santa Fe, New Mexico 87504-2088 SUBJECT.T. Subject Reservoir. IOD NOT USE THE FORM FOR PROPOSALS TO BULL OT O DEEPEN OR PULL OT NOR PERMIT- (FORM CONCORDALT TO BULL OT O DEEPEN OR PULL OT NOR PERMIT- (FORM CONCORDALT TO BULL OT O DEEPEN OR PULL OT NOR PERMIT- (FORM CONCORDALT TO BULL OT O DEEPEN OR PULL OT NOR PERMIT- (FORM CONCORDALT TO BULL OT ODE PERMIT- (FORM CONCORDALTION 1. Type of Well: Somb Fer ON State 2. New of Openace VAILS PERMICHUNCHORDALTION I. Lass News or Usin Agreement Name 105 South 4ch St., Artesia, NM 88210 Kemitz Cisco South/Keemitz Lower Wollcamp I. Device Wollcamp 101 Check Appropriate 30x to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: 11. Check Appropriate 30x to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: 12. New All and rigged to pulling unit. NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: 12. NOTICE OF INTENTION T D: 13. Subana Fe, Jana A	to Approximate Ene., Minerals and Natural Resources Department			Form C-103 Revised 1-1-89
PACE Not 1000, 1001, 1000	DISTRICT 1 OIL CONSERVATION DIVISION			WELL API NO.
P.O. Drever DD, Antels, NM 48210 Stanting DOTRETTING Stanto NM 47410 SUNDRY NOTCES AND REPORTS ON WELLS (DO NOT USE THE FORM FOR USE APPLICATION FOR PERMIP (COMM CONTROLON FOR COROLL OF TO DEEPEN OR PLUB BACK TO A DEFFERENT RESERVOR, USE APPLICATION FOR PERMIP (COMM CONTON FOR COROLL OF FORCESALS) The Walk 1. Type of Walk South Control Content Contreconter Control Control Control Control Contro	F.O. DOX 2088			
TOO Ro Briss Rd, Ame, M 1740 6. State OR & Galax No. LC-3812 LC-3812 (DO NOT USE THE SCOM KOG PROPOSALS TO DIALL OR TO DEFEN GA PLUG BACK TO A. 1. Loc-3812 (DO NOT USE THE SCOM KOG PROPOSALS TO DIALL OR TO DEFEN GA PLUG BACK TO A. 7. Laws Nume or Unk Agreeneed Nume (DO NOT USE THE SCOM KOG PROPOSALS) 1 1. Type of Well: 000000000000000000000000000000000000	DISTRICT II Santa Fe, New Mexico 87504-2088 P.O. Drawer DD, Artesia, NM 88210			5. Indicate Type of Lease STATE X FEE
(DO NOT USE THIS FORM FOR PROPOSALS TO DFILLO RD FOR PERMIT 7. Lass Nume of Unit Agreement Nume (FORM C-10) FOR SUC- PROFOSALS) 7. Lass Nume of Unit Agreement Nume 1. Type of Well 0 0. Main of Openion 8. Well No. 1. TYPE of Well 0 0. More of Openion 8. Well No. 1. Main of Openion 9. Pool same or Wilder! 1. More of Openion 9. Pool same or Wilder! 1. More of Openion 9. Pool same or Wilder! 1. Vall Lesizon 1650 Vall Lesizon 1650 1. Check Appropriate 30x to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON PULO RALTER CASING Comment of Notice, Report, or Other Data NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON PULO RALTER CASING Comment of Notice, Report, or Other Data NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON PULO RALTER CASING Comment of Notice, Repair casing leak OTHER: POID with tubing and Lid down of Noti				
Office Operator Sombrero MS State 2 Name d'Operator 8 Weil No. 1 Addres of Operator 9 Pod anne of Wildat 13 Addres of Operator 9 Pod anne of Wildat 105 South 4th St., Artesia, NM 88210 Kemnitz Cisco South/Kemnitz 4 Weil Location 105 South 4th St., Artesia, NM 88210 Lower WolfCamp Uait Leter . 1650 Feet From Tie South 105 South 4th St., Artesia, NM 88210 Kemmitz Cisco South/Kemnitz Lower WolfCamp 105 South 4th St., Artesia, NM 88210 Kemmitz Cisco South/Kemnitz Lower WolfCamp 105 South 4th St., Artesia, NM 88210 Kemmitz Cisco South/Kemnitz Lower WolfCamp 105 South 4th St., Artesia, NM 88210 Kemitz DF. RRS. RI. GR. etc.) Lower WolfCamp 110 Check Appropriate Osci to Indicate Nature of Notice, Report, or Other Data NOTHCE CF INTENTION TD: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING Comment Subscrept Toole Nature of Notice, Report, or Other Data NOTHER: OrtHER: OrtHER: Completed Proport of Completed Operator (Clearly state all period state, joluting orth. Completed state all period state, joluting ensite all state all period state all period state allest. X	(DO NOT USE THIS FORM FOR PF DIFFERENT RESE (FORM (7. Lease Name or Unit Agreement Name		
YATES PEROLEUM CORPORATION 1 3 Address of Operator 9. Pod same of Wides 105 South 4th St., Artesia, NM 88210 Kennitz Cisco South/Kennitz 4 Wellbackine 1 1650 Feet From Tis 20 Well Location 10. E evalue 1650 Feet From Tis 21 Dit E evalue 165 Stage 335 NMFM Lea 22 Township 165 Evalue 335 NMFM Lea 21 Dit E evalue 10. E evalue 335 NMFM Lea Comp 23 Dit E evalue 10. E evalue 650 Feet From Tis Comp 4195' GR Comp 24 Dit E evalue 10. E evalue 650 Feet From Tis SUBSEQUENT REPORT OF: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING D 0 THER:				Sombrero MS State
1 Address of Operators 10. Produces were Wildear 105 South 4th St., Artesia, NM 88210 Kemnitz Cisco South/Kemnitz 1 Wall Jocation Lower Wolfcamp Unit Letter	-			8. Well No.
105 South 4th St., Artesia, NM 88210 kemnitz Cisco South/Kemnitz 4 Well Locaico Lower Wolfcamp 4 Upit Letter _ J : 1650 Feet From Tie South 1650 Feet From Tie Lower Wolfcamp 4 Well Locaico Lower Wolfcamp Lower Wolfcamp Lower Wolfcamp Sector 22 Township 165 Range 33E NMFM Lea Coury 10 E evalue (Stow whether DF, RED, RT, GR, etc.) 4195' CR 10 Coury 4195' CR 11 Check Appropriate Jox to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TD: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLUANS Coury Course 0THER: Course Course Course Course Course 10.0680'. Load hole with so and pump. Coordeate More asing leak X X 11-6-97 - Tooth with tubing and laid down BHA. Thi who 5-1/2" RBP and packer. Set RBP At todos and pump. Released tubing anchor. Nippled up BOP. Shut in. 11-6-67 / Tested RBP to 1000%. Dig out around wellhead. Fumped down 5-1/2" X 2-7/8". Circulated out 8-5/8'				9 Pool name or Wildcat
4. Well Location Lower Wolfcamp Unit Letter				
Soction 22 Township 165 Range 33E NMPM Lea Courty 10 E varian (Show whather DF, RKB, RT, GR, etc.) 4195' GR 4195' GR 11. Check Appropriate 3ox to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TD: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG ANI) ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DFILLING OPNS. PLUG AND ABANCONMENT PUL OR ALTER CASING COMMENCE DFILLING OPNS. PLUG AND ABANCONMENT CASING TEST AND CEMENT JOB OTHER: Repair casing leak X 12 Desche Proposed or Completed Operations (Charly stat. all perioses desile, and give periosend date, including stained date of staring any proposed X word) SEE RULE 103 and n'igged up pulling unit. Unseat pump. TOOH with rods and pump. 11-4-97 Moved in and rigged up pulling unit. Unseat pump. TOOH with rods and pump. 11-4-97 Noved in and rigged up pulling unit. Unseat pump. TOOH with rods and pump. 11-6-97 TooH with tubing and laid down BHA. TH with 5-1/2" RBP and packer. Set RBP				
10. E craice (Show whether D*, RKB, RT, GR, ac.) 4195' GR 11. Check Appropriate 30x to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T.): SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER. Repair casing leak I2 Describe Proposed or Completed Operations (Clearly stat. all perivers detail, and give perivert date, including estimated date of starting any proposed word J SEE RULE 1003. 11 - 4-97 - Moved in and rigged up pulling unit. Unseat pump. 11-6-97 - Toold with tubing and laid down BHA. TIH with 5-1/2" RBP and packer. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 10000 [#] . Tig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolate holes - top at 5190' and bottom at 5900'. Main holes 5190-	Unit Letter :6	50 Feet From Tie South	Line and16	50 Feet From TheEastLine
10. E craice (Show whether D*, RKB, RT, GR, ac.) 4195' GR 11. Check Appropriate 30x to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T.): SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER. Repair casing leak I2 Describe Proposed or Completed Operations (Clearly stat. all perivers detail, and give perivert date, including estimated date of starting any proposed word J SEE RULE 1003. 11 - 4-97 - Moved in and rigged up pulling unit. Unseat pump. 11-6-97 - Toold with tubing and laid down BHA. TIH with 5-1/2" RBP and packer. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 10000 [#] . Tig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolate holes - top at 5190' and bottom at 5900'. Main holes 5190-	Section 22	Tourstain 165 Pa	nge 33E	NMPM Lea County
11. Check Appropriate 3ox to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION T D: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING OTHER: COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: OTHER: Repair casing leak X I2 Describe Proposed or Completed Operations (Clearly sta. all perimers detail, and give perimers data: including estimated data of staming any proposed X work) SEE RULE 103 na drigged up pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. Shut in. N 11-5-97 - TOOH with tubing and laid down BHA. TIH with 5-1/2" RBP and packer. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 1000#. Dig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing tested to 1000 Fi from 5186' to surface and 6000-10680'. Pumped thru holes 5190- 5766'. Casing tested to 1000 Fi from 5186' to surface and 6000-10680'. <td></td> <td>10. E evalion (Show whether</td> <th>DF, RKB, RT, GR, etc.)</th> <td></td>		10. E evalion (Show whether	DF, RKB, RT, GR, etc.)	
NOTICE OF INTENTION TD: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT OTHER: COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB OTHER: OTHER: Repair casing leak X 12. Describe Proposed or Completed Operations (Clearly star. all perimeri data), including estimated data of staring any proposed X work) SEE RULE 103. In and rigged up pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. Shut in. In and packer. Set RBP at 10680'. Load hole with 85 bbls 2Z - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 1000#. Dig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolated holes - top at 5190' and bottom at 5900'. Main holes 5190- 5766'. Casing tested to 1000 # if rom 5186' to surface and 6000'. Pumped thru hole tom is 51/2" casing and circulate out 8-5/8" X 5-1/2" at 2 BPM at 450 psi. Circulated				
PERFORM REMEDIAL WORK PLUG ANI) ABANDON REMEDIAL WORK ALTERING CASING TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB PLUG AND ABANDONMENT OTHER: OTHER: CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER: CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER: CASING TEST AND CEMENT JOB 11-4-97 Moved in and rigged up pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. Shut in. Shut of the state state the state the state state the state the state state the state state the state the state state state the state state state state the state				-
TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT PULL OR ALTER CASING OTHER: CASING TEST AND CEMENT JOB CASING TEST AND CEMENT JOB OTHER: OTHER: OTHER: Repair casing leak X 12. Describe Proposed or Completed Operations (Clearly stat. all pertinent dates, including estimated date of starting any proposed X 11-4-97 Moved in and rigged up pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. Shut in. 11-6-97 - TooH with tubing and laid down BHA. TIH with 5-1/2" RBP and packer. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 1000#. Dig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolated holes - top at 5190' and bottom at 5900'. Main holes 5190- 5766'. Casing tested to 1000 psi from 5186' to surface and 6000-10680'. Pumped thru hole in 5-1/2" casing and circulate out 8-5/8" X 5-1/2" at 2.5 BPM at 450 psi. Circulated 30 bbls. TIH with 5-1/2" casing and circulate out 8-5/8" X 5-1/2" at 2.5 BPM at 450 psi. Circulated 30 bbls. Circulates out bat of my towkedge md beid.<	NOTICE OF IN	ITENTION TO:	SUE	SEQUENT REPORT OF:
PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: Repair casing leak X 12 Describe Proposed or Completed Operations (Clearly stat. all pertinent details, and give pertinent date, including estimated date of starting any proposed work) SEE RULE 1103. The Repair casing leak X 11-4-97 - Moved in and rigged up pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. Shut in. THEN: TOOH with rods and pump. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-5-97 - Tested RBP to 1000#. Dig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolated holes - top at 5190' and bottom at 5900'. Main holes 5190-5766'. Casing tested to 1000 Fsi from 5186' to surface and 6000-10680'. Pumped thru hole in 5-1/2" casing and circulate out 8-5/8" X 5-1/2" at 2 BPM at 450 psi. Circulated 30 bbls. TIH to 9000'. 11-7-97 - Mixed and spotted 2 stacks 20-40 sand at 9000'. TOOH with tubing. TIH with 5-1/2" cement retainer on tubing to 5150'. Pumped thru retainer. Set retainer. Pressure tested tubing to 2000#. Pressured annulus to 500 psi. Established injection rate thru retainer up 8-5/8" X 5-1/2" at 2.5 BPM at 800 psi. Mixed and pumped 350 sacks Halliburtor Interest centry tool to be at ony troovedge end beldet. CONTINUED ON NEXT PAGE: SUNATURE WILL A SIGNED EY (The space for State UM EP P. N THE OPERATIONER CHOPHAL SIGNED EY (The space f			REMEDIAL WORK	
OTHER:		CHANGE PLANS		G OPNS. PLUG AND ABANDONMENT
Other: Inspect of Completed Operations (Clearly state all periment details, and give periment dates, including estimated date of starting any proposed work) SEE RULE 1103. 11-4-97 - Moved in and rigged tp pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. 'Shut in. 11-5-97 - TOOH with tubing and laid down BHA. TIH with 5-1/2" RBP and packer. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 1000#. Dig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolated holes - top at 5190' and bottom at 5900'. Main holes 5190-5766'. Casing tested to 1000 rsi from 5186' to surface and 6000-10680'. Pumped thru hole in 5-1/2" casing and circulate out 8-5/8" X 5-1/2" at 2 BPM at 450 psi. Circulated 30 bbls. TIH to 9000'. 11-7-97 - Mixed and spotted 2 stacks 20-40 sand at 9000'. TOOH with tubing. TIH with 5-1/2" cement retainer on tubing to 5150'. Pumped thru retainer. Set retainer. Pressure tested tubing to 2000#. Pressured annulus to 500 psi. Established injection rate thru retainer up 8-5/8" X 5-1/2" at 2.5 BPM at 800 psi. Mixed and pumped 350 sacks Halliburton Thereby certify the to formation above is the of ompiete to the for my thereby end belief. CONTINUED ON NEXT PAGE: SUMATURE Operations Technician MAR 2.0 1998	PULL OR ALTER CASING		CASING TEST AND CI	
work) SEE RULE 1103. 11-4-97 - Moved in and rigged up pulling unit. Unseat pump. TOOH with rods and pump. Released tubing anchor. Nippled up BOP. Shut in. 11-5-97 - TOOH with tubing and laid down BHA. TIH with 5-1/2" RBP and packer. Set RBP at 10680'. Load hole with 85 tbls 2% - fluid coming up around casing head. Shut down. 11-6-97 - Tested RBP to 1000#. Dig out around wellhead. Pumped down 5-1/2" X 2-7/8". Circulated out 8-5/8" X 5-1/2". Valve halfway open. Pulled packer up hole testing for casing leak. Isolated holes - top at 5190' and bottom at 5900'. Main holes 5190- 5766'. Casing tested to 1000 µsi from 5186' to surface and 6000-10680'. Pumped thru hole in 5-1/2" casing and circulate out 8-5/8" X 5-1/2" at 2 BPM at 450 psi. Circulated 30 bbls. TIH to 9000'. 11-7-97 - Mixed and spotted 2 sacks 20-40 sand at 9000'. TOOH with tubing. TIH with 5-1/2" cement retainer on tubing to 5150'. Pumped thru retainer. Set retainer. Pressured tested tubing to 2000#. Pressured annulus to 500 psi. Established injection rate thru retainer up 8-5/8" X 5-1/2" at 2.5 BPM at 800 psi. Mixed and pumped 350 sacks Halliburtor Iberdy certify the build information above is tow of my toowledge ad belief. NON NEXT PAGE: SIGNATURE Rust Klein THE OPP MIK FIFTURE P. M	OTHER:		OTHER: Repair	casing leak X
EIFLUREP. N	work) SEE RULE 1103. 11-4-97 - Moved in a: Released tubing anch 11-5-97 - TOOH with at 10680'. Load hol 11-6-97 - Tested RBP Circulated out 8-5/8 for casing leak. Is 5766'. Casing teste hole in 5-1/2" casin 30 bbls. TIH to 900 11-7-97 - Mixed and 5-1/2" cement retain tested tubing to 200 retainer up 8-5/8" X I hereby certify that the Information above is to SKONATURE	nd rigged up pulling unit or. Nippled up BOP. SI tubing and laid down BHA e with 85 tbls 2% - flut to 1000#. Dig out arou " X 5-1/2". Valve half olated holes - top at 5 d to 1000 Fsi from 5186 g and circulate out 8-5 0'. spotted 2 sacks 20-40 s ter on tubing to 5150'. 0#. Pressured annulus t 5-1/2" at 2.5 BPM at 8	it. Unseat pum hut in. A. TIH with 5- id coming up ar und wellhead. way open. Pull 190' and bottom ' to surface an /8" X 5-1/2" at and at 9000'. Pumped thru re to 500 psi. Es 00 psi. Mixed	 ap. TOOH with rods and pump. 1/2" RBP and packer. Set RBP cound casing head. Shut down. Pumped down 5-1/2" X 2-7/8". ed packer up hole testing nat 5900'. Main holes 5190-nd 6000-10680'. Pumped thru 2 BPM at 450 psi. Circulated TOOH with tubing. TIH with etainer. Set retainer. Pressure stablished injection rate thru and pumped 350 sacks Halliburton CONTINUED ON NEXT PAGE:
EIFLUREP. N	(Data space (or State List)	IAL SIGNED EY	· · · · · · · · · · · · · · · · · · ·	
APPROVED BY TITLE TITLE	1	Children Address		MAR 2 0 1998
	APTROVED BY	π	LE	