

N. M. OIL CONS. COMMISSION  
P. O. BOX 1030  
HOBBS, NEW MEXICO 88240

Form 9-331  
Dec. 1973

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other CO<sub>2</sub> injection

2. NAME OF OPERATOR  
CONOCO INC.

3. ADDRESS OF OPERATOR  
P. O. Box 460, Hobbs, N.M. 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2600' FNL & 660' FEL  
AT TOP PROD. INTERVAL: ☒  
AT TOTAL DEPTH: ☒

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☒  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Tie-back liner

SUBSEQUENT REPORT OF:

RECEIVED

APR 26 1983

OIL & GAS  
MINERALS MGMT. SERVICE  
ROCHELLE, NEW MEXICO

(NOTE) Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Verbal approval by Peter Chester 4/25/83.  
Rel. dual pkr. @ 3577'. Circulate well w/ high salinity brine to minimize CO<sub>2</sub> Kicks. Set RBP @ 3575'. Spot 4 SX. sand on top of RBP. Polish and mill tie-back receptacle. GIH w/ tie-back stem on bottom of 1 jt of 7 5/8" 33.7# L-80 casing, comb. float collar, 1 jt. of 7 5/8" 33.7# L-80 csg. and approx. 3465' of 7 5/8" 26.4# K-55 csg. Land tie-back stem in receptacle until first rubbers, are felt. Pull up approx. 2'. Establish circulation by pumping 20 bbls. fresh water as pad. Cmt. to surface w/ 710 SXS. Cl. 'H' cmt. Land tie-back stem into tie back receptacle. W.O.C. 24 Hrs. D.O. comb. float collar-landing collar & cmt. Circ. clean. Rel. RBP. Run inj equip.  
Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Greg Perry TITLE Administrative Supervisor DATE 4/25/83

APPROVED

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

MAY 2 1983

MAY 1 1983

HOBBS OFFICE