ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
AA	Primary Cutout - 100 amp, 15 KV, 16000 amp int. cap.	F2XX1015G			X
BB	General Purpose "U" bolt Clamp	UC510AGP			
CC	Lightening arrestor, 10 KV				
DD	Single phase oil switch, 14.4 KV			McGRAW-EDISON KVMC 2	
EE	split bolt connector, size req'd			BLACKBURN "C" SERIES	
FF	grounding specs. see dwg No. ES-11 & ES-1A, Note 3				
GG	35' class 4 creosoted pine pole				
HH	Aluminum deadend Preforms for ACSR, size req'd				
II	30' class 6 creosoted pine pole				
JJ	OPEN HEAD GRND, #4 ACSR - If Req'd - Ref. Dwg ES-11, ES-1A - Note 3				
KK	ground connector, motor			BURNDY KC-22	X
LL	600 V. secondary lightening arrestor single phase				
MM	Greenfield Type EF liquid-tight flexible steel conduit, size req'd, w/ necessary liquid-tight connectors.				
NN	req'd size LB fitting & cover & gasket				
OO	transformer tank grounding terminal	GW3-15			
PP	Bird Guards (Insulating boots on transformer bushings)			WESTINGHOUSE - [illegible]	

DATE: 12-27-71	TITLE: DESCRIPTION MATERIAL
DRAWN BY: E. WINTER	
DESIGN BY:	conoco
CHECKED BY:	PRODUCTION DEPT. HOBBS DIVISION
APPROVED BY:	JOB: ELEC SPECS / DRAWING NO.: ES-1
SCALE: NONE	SHEET 2 OF 3