

ITEM	DESCRIPTION	A. B. CHANCE NO.	JOSLYN NO.	OTHER MFRS. NO.	NO SUB.
a	double upset bolt w/sq. nut, round washer, and corner key on short end, sq. nut and w/ locknut on long end, 15 1/8" long (or length required.)	7828			
b	wet process porcelain secondary spool insulator, 3" - brown glaze		1101		
d	required size conduit w/ servicehead(s) & req'd size & rated insulated conductors. Ref. Dwg ES-1B Note: provide clamp and ground conduit parallel groove clamp, size req'd			BURUNDI SERIES "UC"	
e	secondary insulator clevis for 4" insulator				
f	3/4" thinblye nut	6510			
h	5/8" x 12" (or length req'd) straight thinblye bolt w/sq. nut	5512			
j	transformer cluster mount bracket (small)			ALUMA FORM 6M3-6	X
l	transformer cluster mount bracket (large)			ALUMA FORM 6M3-6	X
m	req'd size raintight disconnect & fuses, 3-phase, 600 V. Ref. Dwg No. ES-1B				
n	16" cross plate anchor (or size req'd)	X-16			
q	4-way expanding anchor (size req'd)	88135			
c	4" brown glaze wet process porcelain secondary spool insulator		10101		
u	5/8" x 7" thinblye anchor rod w/nut (use thinblye if req'd - Chance No. 5377)	5317 (NUT 55006P)			
aa	3/4" high strength guy strand (10,800 lb.)				
bb	prefabricated guy grip for 3/8" guy strand				
ai	5/8" x 10" angle thinblye bolt w/nut	5010			X
cc	3"x3"x1/4"x11/16" hole curved washer	6823 1/2			
ff	6" - guy clamp w/3-1/2" bolts				
ee	7" x 10" size strain insulator				
yy	servicing sleeve for 3/8" guy strand	6454			
ii	3 1/2" x 2 1/2" x 7" lift plate	7887			X
nn	pole bottom ground plate (may use butt-wrapp if desired)				
qq	round connection (See Dwg. ES-12)				
rr	wet process porcelain secondary spool insulator, 3" - white glaze				
tt	wet process porcelain secondary spool insulator, 4" - white glaze				

TITLE: DESCRIPTION MATERIALS	
DATE: 12-27-71	
DRAWN BY: E. WINTER	
DESIGN BY:	
CHECKED BY:	
APPROVED BY:	
SCALE: NONE	

CONOCO

PRODUCTION DEPT.

HOBBS DIVISION

DRAWING NO.

ES-1

ELEC SPECS

SHEET 3 OF 3