

CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.B.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-4109	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator

Arrowhead Oil Corporation

Address of Operator

P. O. Box 548, Artesia, New Mexico 88210

Location of Well

UNIT LETTER C 330 FEET FROM THE North LINE AND 2309.3 FEET FROM
THE West LINE, SECTION 32 TOWNSHIP 17-S RANGE 32-E N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

Wallingford

9. Well No.

#2

10. Field and Pool, or Wildcat

Mal-jamar

11. Elevation (Show whether DF, RT, GR, etc.)

3906' GL

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐PLUG AND ABANDON ☐REMEDIAL WORK ☐ALTERING CASING ☐TEMPORARILY ABANDON ☐COMMENCE DRILLING OPNS. ☒PLUG AND ABANDONMENT ☐REPAIR OR ALTER CASING ☐CHANGE PLANS ☐CASING TEST AND CEMENT JOBS ☒OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 5:15 PM on March 11, 1980. Ran 23 joints of 8 5/8" 24# casing and set at 920' KB. Cemented with 200 sacks of Class C 2% CaCl cement and circulated. Pressure tested to 500# and held for 30 minutes. Test OK. Waited on cement 18 hours and drilled to T.D. with 7 7/8" bit.

Ran 4216' of 4 1/2" 10.5# CW-55 casing with DV Tool set @ 1748'. Cemented with 620 sacks of Class H cement w/5# salt and 10# sand and 50 sacks of Class C Neat cement. Opened DV Tool and circulated. Pumped 500 sacks of Halliburton Light Cement W/10# Gilsonite and 15# salt and 100 sacks of Class C 4% CaCl thru DV Tool. Pressure tested to 1000#. Tested OK.

Started in hole with bit and scraper and drilled to 1747' and had water flow. Rigged up Halliburton and squeezed with 300 sacks of Class C 4% CaCl cement and pressure tested OK. Drilled out cement and DV Tool with no water flow.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WED Melvin A. LopezTITLE SecretaryDATE April 3, 1980

Orig. Signed by

Jerry Sexton

APPROVED BY _____

TITLE _____

DATE _____

NOTATIONS OF APPROVAL, IF ANY: