U.3.0.5. Sh. Indicate Type of Leases LAND OFFICE State OIF 6 Cost DPERATOR State OIF 6 Cost Lease No. APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK To Brite Cost Lease No. * Type of Weak To Brite Cost Lease No. * Type of Weak To Brite Cost Lease No. * Type of Weak To Brite Cost Lease No. * Type of Weak To Brite Cost Lease No. * Type of Weak State OIF 6 Cost Lease No. * Type of Weak State Cost State OIF 6 Cost Lease No. * Weak Cost State OIF 6 Cost Lease No. State Cost State OIF 6 Cost Lease No. * More at Departor State Cost State OIF 6 Cost Lease No. * Address of Operator State Cost State OIF 6 Cost Lease No. * Use State OIF 6 Cost Lease No. State Cost State OIF 6 Cost Lease No. * Address of Operator State Cost State OIF 6 Cost Lease No. * Address of Operator State Cost State OIF 6 Cost Lease No. * Address of Operator State OF 6 Cost Lease No. * Address of Cost State OF 6 Cost Lease No. State OF 6 Cost Lease No. * Cost State OF 6 Cost State OF 6 Cost Lease No. State OF 6 Cost Lease No. * Cost State OF 6 Cost State Plas No. State OF Cost State OF	NO. OF COPIES RECEIVED				B	i -02	5-36740
-ATT RE	DISTRIBUTION	NEW	MEXICO OIL CONSE	RVATION COMMISSION	1 5	orm (C-10)	
Unit G.S. Interface ret [E] CAND OFFICE ret [E] ret [E] CAND OFFICE ret [E] ret [E] CAND OFFICE PLUC BACK ret [E] Type of Watt DELL [X] DEPEN [PLUC BACK Type of Watt DELL [X] DEPEN [PLUC BACK Watt [X] State Type of Watt Ret ret [X] Watt [X] State Type of Watt Ret ret [X] Watt [X] State Type of Watt Ret ret [X] Watt [X] State Type of Watt Ret ret [X] Watt [X] State State State Watt [X] State State State A00 Wilco Building, Midland, Texas [7970] Caudill-Devonian State Caudifier State State State 990 ret return [West] Use 252 9 Tap 15-5 State State 132.1 State State State State State State 132.2 State State State State State State State <td>ANTA FE</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td>65</td>	ANTA FE						65
U.S.G.S. Fact Difference Fact Difference Fact Difference APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Agreement Name APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Agreement Name Type of Name Billing DEEPEN PLUG BACK Type of Name Billing DEEPEN PLUG BACK 7. Unit Agreement Name Moran Exploration, Inc. Cannot State Cannot State 10. Factor and State Moran Exploration, Inc. 11. Factor and Protect and State 11. Factor and Protect and State Moran Exploration, Inc. 11. Factor and Protect and State 11. Factor and Protect and State 900 ref react and State 2310 ref react and North 12. Active and Protect and State 920 ref react and State 2310 ref react and North 12. Active and Protect and State 921 ref react and North 12. Active and Protect and North 12. Active and Protect and North 12. Active and Protect and North 1. Considered Weil Protein Processes 9 ref react and North 12. Active and Protect and North 12. Active and Protect and North 1. Considered Weil Protein Processes 13. Active and Protect and North 13. Activ	FILE					A. Indicate	Type of Lease
LAND OFFICE S. Rither OI & Gona Lesses No. PERATOR APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Agreement Nome a type of Nome PRUL I I I I I I I I I I I I I I I I I I I	U.S.G.S.					ſ	
APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK 7. Unit Adversent Hend Type of Work 7. Unit Adversent Hend Attract Series 0. Notes Type of Work 8. Form on Leade Nones Type of Work 10. Experience Moran Exploration, Inc. 2 Address of Spendar 11. Ford and Power explored to	LAND OFFICE					·	
Prove of Wark DRUL X DEEPEN PLUG BACK ¹² Unit Agreement Note: Noran Exploration, Inc. ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: 400 Wiles Building, Milland, Texas 79701 ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - GL 3922.1 ¹² Unit Agreement Note:	OPERATOR						a das Etase no.
Prove of Wark DRUL X DEEPEN PLUG BACK ¹² Unit Agreement Note: Noran Exploration, Inc. ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: 400 Wiles Building, Milland, Texas 79701 ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - GL 3922.1 ¹² Unit Agreement Note:					k	m	mmmm
Prove of Wark DRUL X DEEPEN PLUG BACK ¹² Unit Agreement Note: Noran Exploration, Inc. ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: Address of Operator ¹² Unit Agreement Note: ¹² Unit Agreement Note: 400 Wiles Building, Milland, Texas 79701 ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - Seen agreement ¹² Unit Agreement Note: ¹² Unit Agreement Note: ¹² Unit Agreement Note: - GL 3922.1 ¹² Unit Agreement Note:	APPLICATION FOR PERMIT TO DRILL DEEPEN OR RULE DACK						
DRUL I DEEPEN PLUG BACK A fram of Lotse Name A fram of Lotse Name	la, Type of Work		DRIEL, DELLEN, C	JILT LUG BACK			
And the set of the set o		7				· Onic Agre	ement Name
Others of Operator Matter of Operator Matter of Operator Operator Matter of Operator Operator <thoperator< th=""> Operator <thoperator<< td=""><td>b. Type of Well DRILL X</td><td>Ĺ</td><td>DEEPEN</td><td>PLUG B</td><td></td><td></td><td></td></thoperator<<></thoperator<>	b. Type of Well DRILL X	Ĺ	DEEPEN	PLUG B			
Notan Exploration Source Texit Cann Address of Coperator 10. Protocol Society Soc		ן				. Farm or L	.ease Name
Moran Exploration, Inc. 2 Address of Operator 10. Field and Proof, or Wilcomt 400 Wilco Building, Midland, Texas 79701 10. Field and Proof, or Wilcomt 1. Location of Well Wirt certure Wirt certure Wirt certure 990 recerceson ter West Like or sec. 9 recerceson ter West 10. Found and Proof, or Wilcomt 2. Section of Well Wirt certure Wirt certure 9 recerceson ter West 10. Found and Proof, or Wilcomt 2. Section of Well Wirt certure Wirt certure 9 recerceson ter West 10. Found and Proof, or Wirth tere 2. Section of Well Wirt certure 9 recerceson ter West 10. Found and Proof, or Wirth tere 2. Section of Well Wirt certure 9 recerceson ter West 10. Found and Proof, or Wirth tere 2. Section of Well Wirt certure 11. Foundation 10. Found and Proof, or Wirth tere 2. Section of Well Blanket-Current Not determined March 31, r 1980 2. Section State Flags data 11. 715 Devonian Recervire 3. Size of HOLE Size of CASING WellGHT PER FOOT Section Tervire March 31, r 1980		O HER			ZONE		
Address of Operator 10. First and Peol, or Wildow 4000 Wilco Building, Midland, Texas 79701 10. First and Peol, or Wildow Location of Well Wit CTTER 2310 990 recorrect to West Incorrect 2310 990 recorrect to West Incorrect 2310 12. Country I. Country I. Country 13. Frequent Legs. 13. Frequent Legs. 14. End 13. Frequent Legs. 13. Frequent Legs. 14. End 13. Frequent Legs. 13. Frequent Legs. 12. Approx. Data Vary of C.T. 14. Edge 13. Frequent Legs. 13. Frequent Legs. 12. Approx. Data Vary of C.T. 15. Childs John Chemined 13. Frequent Legs. 13. Frequent Legs. 12. Approx. Data Vary of C.T. 15. Childs John Middle Wester Dit, RT. etc.) 13. Kind 6 State Flex Floot 12. Environ. 22. Approx. Data Vary of C.T. 15. Childs John Middle Wester Dit, RT. etc.) 13. Kind 6 State Flex Floot 12. Formation 22. Approx. Data Vary of C.T. 17. Childs Childs Above Mark Middle Current Not determined March 31. 1980 22. Approx. Data Vary of C.T. 17. Childs Childs Above Above Algo Mark Middle Current Not determined March 31. 5 15. 5 <td>•</td> <td></td> <td></td> <td></td> <td></td> <td>. Well No.</td> <td></td>	•					. Well No.	
400 Wilco Building, Midland, Texas 79701 Ib. Feed and Feel, at Wildowt Lacontion of Well with Littles 2310 rest resource, North Little 990 rest resource, West concerns; 9 rest, 15-5 sec. 36E with Littles 10 rest resource, West concerns; 9 rest, 15-5 sec. 36E with View 110 rest resource, West concerns; 9 rest, 15-5 sec. 36E with View 110 rest resource, West concerns; 9 rest, 15-5 sec. 36E with View Lea 110 rest resource, West concerns; 9 rest, 15-5 sec. 36E with View Lea 111 rest resource, West 132, resource, 15-5 sec. 162, Append. Date View View View Lea 111 rest resource, View View 132, 150 Devonian Not determined March 31, resource, 75 111 rest resource, View View Not determined Not determined March 31, resource, 75 112/2 13 3/8 SiZE OF HOLE SiZE OF CASING AND CEMENT PROGRAM SiZE OF FOLE SiZE OF CASING AND CEMENT PROGRAM<	Address of Operator	ration, Inc.				2	
Lecention of Weil Diff Letters	•		•			0. Field an	d Pool, or Wildcat
Second Name Out Letters O E Letter ADD Second Name North Line 990 reservator Te West Letter Second 36E Janne	400 Wilco Bi	ilding, Midlar	<u>nd, Texas 79701</u>			Caudil]	l-Devonian
990 recerce record the West Unit of size. 9 rever 15-5 ris. 36F rever 12. Country Lea 12. Country Lea 12. Country Lea 12. Country Lea 13.715 13.715 Devoid 100,05 10.4. Formation 12. Country Lea 13.715 Devoid 100,05 Devoid 100,05 22. Appendent of C.T. 12. Country Blanket-Current Not determined March 31, 71980 22. Appendent weilt weilt weilt weit weilt weiter SiZE OF HOLE SiZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% 13.3/15 3600 Surface 12% SiZE OF HOLE SiZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% 13.3/16 Surface 12% 8 5/8 24# & 32# 4700 300 3600 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13.3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 1 7/8'' hole to 13800' run and cement 5½'' casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours.	UNIT LETT	ER LOC	ATED 2310	EET FROM THE North	N. 1	\overline{M}	<u>MMMMMM</u>
10. Proposed best 10							
12. Soundy Lea 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 715 13. 7198 13. 7198 Not determined March 31. 7 1980 PROPOSED CASING AND CEMENT PROGRAM Size of AOLE Size of AOLE Size of AOLE Size of AOLE Size of CASING WEIGHT PER FOOT SETTING CEPTH Advance Devolution Solution So	990 FEET FROM	THE West LIN	EOFSEC. 9 TV	<u>VP. 15-</u> S RGE. 3	5E NMPM	IIIII	
113. Proposed Lop.1. 114. Formation 20. Rotary or C.T. Retary 13. 715 Devonian Rotary CL 3922.1 Blanket-Current 13. 715 Devonian Rotary Not determined 22. Approx. Date Work will start March 31.5 DBOOM March 31.5 DBOOM PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP THE SIZE OF CASING MUCHARASING AND CEMENT PROCEADA		THHHHHHH,	TITTITI IIIIIIIIIIIIIIIIIIIIIIIIIIIIII	<u>IIIIIIIIIIIIII</u>		2. County	··· XIIIIII
113. Proposed Lop.1. 114. Formation 20. Rotary or C.T. Retary 13. 715 Devonian Rotary CL 3922.1 Blanket-Current 13. 715 Devonian Rotary Not determined 22. Approx. Date Work will start March 31.5 DBOOM March 31.5 DBOOM PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17% SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP THE SIZE OF CASING MUCHARASING AND CEMENT PROCEADA						Lea	VIIIIII
13,715 Devoian Rotary CL 3922.1 ELA KING & STATE PLAD. BOLL 216. Device and the state Plad. Boll 22. Approx. Due Wark will stort Blanket-Current Not determined March 31,5 1980 PROPOSED CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17½ 13 3/8 4 48# 400 400 Surface 12½ 8 5/8 24# & 32# 4700 300 3600 7 7/8 5 ½ 17# 13 3/8 48# A 13 3/8 48# 400 400 Surface 11½ 13 3/8 48# 12½ 8 5/8 24# & 32# 4700 300 300 3600 12½ 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# <			<u>illillillilli</u>		HHHH		/////////////////////////////////////
13,715 Devoian Rotary CL 3922.1 ELA KING & STATE PLAD. BOLL 216. Device and the state Plad. Boll 22. Approx. Due Wark will stort Blanket-Current Not determined March 31,5 1980 PROPOSED CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17½ 13 3/8 4 48# 400 400 Surface 12½ 8 5/8 24# & 32# 4700 300 3600 7 7/8 5 ½ 17# 13 3/8 48# A 13 3/8 48# 400 400 Surface 11½ 13 3/8 48# 12½ 8 5/8 24# & 32# 4700 300 300 3600 12½ 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# 17# <		///////////////////////////////////////	///////////////////////////////////////		////////	//////	///////////////////////////////////////
13,715 Devonian Rotary GL 3922.1 21A. Kind & Elfus Elus, Beal 21B. Cellus Constant 22. Approx. Date Work will stort Blanket-Current Not determined March 31, 1980 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17 ¹ /2 13 3/8 48# 400 400 Surface 12 ¹ /2 8 5/8 24# & 32# 4700 300 3600 7 7/8 5 ¹ /2 17# 13800 800 10000 Drill 17 ¹ /2' to 1000 psi for 30 minutes. Drill 17 ¹ /2' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 17 ¹ /2' hole to 4700' cement 8 5/8'' casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8'' hole to 13800'' run and cement 5 ¹ /2'' casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. <td></td> <td>MMMMM</td> <td><u> </u></td> <td>9. Proposed Depth 19</td> <td>A. Formation</td> <td>11111</td> <td>20. Rotary or C.T.</td>		MMMMM	<u> </u>	9. Proposed Depth 19	A. Formation	11111	20. Rotary or C.T.
Constructs (show whether DF, RT, etc.) 21A. Kind & Strike Pluy. Sond 21B. Drilling Constant 22. Approx. Date Work will start GL 3922.1 Blanket-Current Not determined March 315 1980 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17½ 13 3/8 48# 400 400 Surface 12½ 8 5/8 24# & 32# 4700 300 3600 7 7/8 5½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12½" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. NOVE SPACE DESCRIBE PROPOSED PROGRAM. IF PROPOSED AND ACCEPT OF PROGRAM. IF ANY. Not describe proposed proof PROGRAM. IF PROPOSED AND RECEPT OF PROGRAM. IF ANY.			<i>WIIIIIIIIII</i>	1			-
GL 3922.1 Blanket-Current Not determined March 31, 1980 March 31, 1980 PROPOSED CASING AND CEMENT PROGRAM SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17½ 13 3/8 48# 400 400 Surface 12½ 8 5/8 24# & 32# 4700 300 3600 7 7/8 5 ½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12½" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. AMOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL 15 TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE AND PROPOSED NEW	. Elevations (Show whether DF	, RT, etc.) 21A. Kind	& Status Plug. Bond 21			22. Aprilar	
PROPOSED CASING AND CEMENT PROCRAM SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17½ 13 3/8 48# 400 400 Surface 12½ 8 5/8 24# & 32# 4700 300 3600 10000 7 7/8 5 ½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12½'' hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8'' hole to 13800' run and cement 5½'' casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours.	GL 3922.1	Blanket					
SIZE OF HOLE SIZE OF CASING WEIGHT PER FOOT SETTING DEPTH SACKS OF CEMENT EST. TOP 17½ 13 3/8 48# 400 400 Surface 12½ 8 5/8 24# & 32# 4700 300 3600 7 7/8 5 ½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) . Test Csg. to 1000 psi for 30 minutes. Drill 12½'' hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. . Drill 7 7/8" hole to 13800' run and cement 5½'' casing with sufficient cement to fill annulus above any producing zone. . . Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. . ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OF PLUG BACK, GIVE DATA ON PRESENT PRODUctive ZONE AND PROPOSED NEW PRODUctive ZONE AND PROPOSED NEW PRODUctive Textverter PROPOSED NEW PRODUctive Textverter PROPOSED PROGRAM: IF ANY. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OF PLUG BACK, GIVE DATA ON PRESENT PRODUctive ZONE AND PROPOSED NEW PRODUctive ZONE AND PROPOSED NEW PRODUctive ZONE AND PROPOSED NEW PRODUctive Conditions and will be tested not less than once each 24 hours.	3.					riar Cil	JI 5 1900
1712 13 3/8 48# 400 2011 BACKSOF CEMENT EST. TOP 1212 8 5/8 24# & 32# 4700 300 300 3600 7 7/8 5 ½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12½'' hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13600' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE AND PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE AND PROPOSED NEW P		P	ROPOSED CASING AND	CEMENT PROGRAM			
1712 13 3/8 48# 400 2011 BACKSOF CEMENT EST. TOP 1212 8 5/8 24# & 32# 4700 300 300 3600 7 7/8 5 ½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12½'' hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13600' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OF PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE AND PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE AND PROPOSED NEW P	SIZE OF HOLE	SIZE OF CASING	WEIGHT BED FOOT				
124 8 5/8 24# & 32# 4700 300 3600 7 7/8 5 ½ 17# 13800 800 10000 Drill 17½' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12¼'' hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½'' casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRCOU Flowet alle dowout preventers will be used to the best of my knowledge and bellst. Test case the information above is true and complete to the best of my knowledge and bellst. Title						CEMENT	
7 7/8 5 1/2 17# 13800 800 10000 Drill 17/2' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12/2'' hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, Give DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE THE PROD							
Drill 17 ¹ / ₂ ' hole to 400' (Through fresh water zones) cement 13 3/8 Csg. (Circulate) Test Csg. to 1000 psi for 30 minutes. Drill 12 ¹ / ₄ " hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5 ¹ / ₂ " casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours.		5 1					
Test Csg. to 1000 psi for 30 minutes. Drill 12¼" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Treby certify that the information above is true and complete to the best of my knowledge and bellsf. True	/ //8	52	17#	13800	800		10000
Test Csg. to 1000 psi for 30 minutes. Drill 12¼" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Treby certify that the information above is true and complete to the best of my knowledge and bellsf. True			'	1	1	1	
Test Csg. to 1000 psi for 30 minutes. Drill 12¼" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. Treby certify that the information above is true and complete to the best of my knowledge and bellsf. True	Drill 17½' hole	to 400' (Throug	h fresh water z	zones) cement 13	3/8 Csg	. (Circ	ulate)
Drill 124" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E TONE. GIVE BLOWOUT PREVENTER PROPOSED PROGRAM. IF ANY. reby certify that the information above is true and complete to the best of my knowledge and belisf. med <u>ALMANAMM</u> <u>Title</u> Chief Clerk-Office Manager <u>Date</u> March 12, 1980	•			,	-,	. (0110	/
Drill 124" hole to 4700' cement 8 5/8" casing and test to 1500 psi for 30 minutes. Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E TONE. GIVE BLOWOUT PREVENTER PROPOSED PROGRAM. IF ANY. reby certify that the information above is true and complete to the best of my knowledge and belisf. med <u>ALMANAMM</u> <u>Title</u> Chief Clerk-Office Manager <u>Date</u> March 12, 1980	. Test Csg. to 100)0 psi for 30 mi	nutes.				(
Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. reby certify that the information above is true and complete to the best of my knowledge and bellsf. med <u>H. M. March 12, 1980</u> Title Chief Clerk-Office Manager <u>Date March 12, 1980</u>		•)
Cement to be circulated to surface. Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM. IF ANY. reby certify that the information above is true and complete to the best of my knowledge and bellsf. med <u>H. M. March 12, 1980</u> Title Chief Clerk-Office Manager <u>Date March 12, 1980</u>	Drill 12 ¹ 4" hole	to 4700' cement	: 8 5/8" casing	and test to 150) nei fo	r 30 mi	nutor V
Drill 7 7/8" hole to 13800' run and cement 5½" casing with sufficient cement to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours.	Cement to be cir	culated to surf	ace.		0 psi 10	1 30 111	nuces.
to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. reby certify that the information above is true and complete to the best of my knowledge and belief. Title Chief Clerk-Office Manager Date March 12, 1980							
to fill annulus above any producing zone. Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours. ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU E ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY. reby certify that the information above is true and complete to the best of my knowledge and belief. Title Chief Clerk-Office Manager Date March 12, 1980	. Drill 7 7/8" hol	e to 13800' rur	and cement 51/1	Casing with a	ifficiant		+
Proper blow-out preventers will be used to sufficient capacity to meet all down hole conditions and will be tested not less than once each 24 hours.	to fill annulus	above any produ	cing zong	casing with St	tent	cemen	L
hole conditions and will be tested not less than once each 24 hours.	annordo	produ	cing some.				
hole conditions and will be tested not less than once each 24 hours.	Proper blow-out	proventore will	he was he and	· · · · ·			
ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODU zone. give blowout preventer program, if any. reby certify that the information above is true and complete to the best of my knowledge and belief. med <u>July March 12</u> , 1980 Title Chief Clerk-Office Manager Date March 12, 1980	bole conditions	and will be too	ted used to sur	licient capacit	y to mee	t all d	own
reby certify that the information above is true and complete to the best of my knowledge and belief. med <u>J. C. Jacogguno</u> <u>Title</u> Chief Clerk-Office Manager <u>Date</u> March 12, 1980	noie condicions	and will be tes	Led not less th	ian once each 24	hours.		
reby certify that the information above is true and complete to the best of my knowledge and belief. med <u>J. C. Jacogguno</u> <u>Title</u> Chief Clerk-Office Manager <u>Date</u> March 12, 1980							
reby certify that the information above is true and complete to the best of my knowledge and belief. med <u>J. C. Jacogguno</u> <u>Title</u> Chief Clerk-Office Manager <u>Date</u> March 12, 1980							
reby certify that the information above is true and complete to the best of my knowledge and belief. med <u>Ju E Jonegquins</u>	ABOVE SPACE DESCRIBE PR E ZONE, GIVE BLOWOUT PREVENT	OPOSED PROGRAM: IF P	ROPOSAL IS TO DEEPEN OR	PLUG BACK, GIVE DATA ON	PRESENT PRODU	CTIVE ZONE	AND PROPOSED NEW PRODU
And A. P. Scroggins Chief Clerk-Office Manager Date March 12, 1980					• ••• ••• ••• •••		
	reby certify that the information		lete to the best of my knp	owledge and belief.			
	ereby certify that the informatio	n above is true and comp					
PROVED BY	ereby certify that the information	•	Tila Chief Cle	rk-Office Manao	er -	Marc	h 12 1980
PROVED BY ALLECTATION TITLE SUPERVISION DATE MARINE DATE	ned for For	oggins	TuleChief Cle	rk-Office Manag	er Da	e Marc	h 12, 1980
DITIONS OF APPROVAL, IS ANY	ned for For	oggins	TitleChief_Cle	rk-Office Manag	er Dat	e <u>Marc</u>	h 12, 1980
IDITIONS OF APPROVAL, IF ANY	ned for For	oggins	TuleChief_Cle	rk-Office Manag	er Da	e Marc	h 12, 1980
	ned for For	oggins	Tule_Chief Cle	rk-Office Manag	er Da	e <u>Marc</u>	h 12, 1980
	ned J. F. Sor	oggins	Title Chief Cle	rk-Office Manag	per Da	e Marc	h 12, 1980
	red Ju E Sor	oggins	Title Chief Cle	rk-Office Manag	Da	e <u>Marc</u>	h 12, 1980