

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-26854
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Lease Name or Unit Agreement Name Leavelle
2. Name of Operator Gandy Corporation	
3. Address of Operator P. O. Box 827, Tatum, NM 88267	8. Well No. 1
4. Well Location Unit Letter <u>B</u> : <u>660</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line Section <u>23</u> Township <u>16S</u> Range <u>35E</u> NMPM <u>Lea</u> County	9. Pool name or Wildcat N. Shoe Bar Wolfcamp
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3984.5' KB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: Convert to Disposal ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Squeeze Wolfcamp perms 10298'-10308' with 100 sxs Class H cement. Drill out squeeze and test to 500 psi.
2. Drill out CIBP's at 11250', 11800', and 12050'.
3. Drill out casing shoe. Drill new 4 3/4" hole from 12160' to 12700'.
4. Acidize Devonian with 3000 gals 15% HCL.
5. Perforate 5 1/2" casing at 9750'. Circulate cement up to 4160' between 5 1/2" and 8 5/8" casing.
6. Run Model R packer and 2 7/8" internally plastic coated tubing and set at 11575'. Load backside with packer fluid.
7. Commence water disposal into Devonian.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Marc Wise TITLE Agent DATE 4/1/92
TYPE OR PRINT NAME Marc Wise TELEPHONE NO 392-6950

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL IF ANY

APR 06 '92