Elevation 3984.5' RKB LEAVELLE NO. 1 PROPOSED WELLBORE 3/31/92 0 17 1/2" Hole Size 7 423' — 13 3/8", 86#, H-40 Casing
Cemented w/500 axs Class "C" + add.
Circulated 75 axs to surface 11" Hole Size ◺ 4 4260' - 8 5/8", 24 & 32#, K-55 Cosing Cemented w/1200 sxs Howco Lite followed by 200 sxs Class "C" + add. Circulated 250 sxs to surface 7 7/8" Hole Size 2 7/8", 6.5%, N-80 Tubing Internally Plastic Coated (PROPOSED) Perf @ 9750' and circulate cement up to 4160' (PROPOSED) Perf @ 10240' and squeeze w/100 sxs cement Perfs 10298'-308' (Wolfcamp) Squeeze w/100 sxs Cement – Baker Model "R" Packer \varTheta 11575' Perfs 11676'-84' (Morrow "A") Perfs 11932'-34', 11936'-49' (Morrow) - Squeezed 12/80 Perfs 12091'-12102' (Mississippion) 12160' - 5 1/2", 17 & 23#, N-80 & S-95 Casing Cemented w/ 500 sxs Class "H" + 5#/sx KCL + add. Top of Devonian ±12425 4 1/2 O.H. 12160'-12700' (PROPOSED) GANDY CORPORATION T.D. 12700' (PROPOSED) Leavelle No. 660' FNL & 1980 FEL Section 23. T-16S. R-35F Lea County, New Mexico