STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

we. of Carles Accelves	1	
DISTRIBUTION		
SANTAPE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

OIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 -

SANTA PE	SANTA FE, NEW MEXICO	87501 Revise	d 10-1-78
FILE			
U.\$.G.\$.	_]	Sa. Indicate Type of Lease	
LAND OFFICE		State [_]	Foo X
OPERATOR		5, State Oil & Gas Lease No	0.
USE "APPLICAT	RY NOTICES AND REPORTS ON WELLS OPEN ON PLUG BACK TO A DIFFER TION FOR PLUG BACK TO A DIFFER TION FOR AUCH PROPOSALS.	SENT RESERVOIR.	
OIL GAB WELL X	OTHER•	7, Unit Agreement Name	
2. Name of Operator	1. Name of Operator		
U. S. Operating, Inc.		Leavelle	
2709 N. Big Spring Street; Midland, Texas 79701		3. West 110,	
4. Location of Well	Location of Well		
	((0	10. Field and Pool, or Wildo	at
UNIT LETTERB	660 FEET FROM THE North LINE AND	1980 Undesignated	
THE East LINE, SECTION	on 23 TOWNSHIP 16S RANGE 15. Elevation (Show whether DF, RT, GR, et 3984, 5 RKB		
Check		i Pa (IIII)	'77/77
NOTICE OF IN	Appropriate Box To Indicate Nature of Not	SUBSEQUENT REPORT OF:	
PERFORM REMIDIAL WORK TEMPORARILY ABANDON FULL OR ALTER CASING OTHER	f	ACIENING CASING	MENT

17. Descrite Froposed or Completed On	perations (Clearly state all pertinent details, and give pe		
work) SEE RULE 1103.		runent dates, including estimated date of starting any	proposed
1 0-211-1-111	olo to 42601 - 11		
i incritora ilii ba	310 to 1016111 ad the cate and 111		

- Drilled II" hole to 4260' with saturated brine water.
- 2. Ran 108 joints of new 8-5/8", 24# & 32#, K-55 casing to 4260'.
- Halliburton cemented in 1 stage with 1200 sacks of Halliburton Light with 15# salt per sack, 1/4# Flocele per sack and 5# Gilsonite per sack. Tailed in with 200 sacks of Class C with 1/4# Flocele and 5# Gilsonite per sack.
- Observed full returns while cementing and circulated 250 sacks to pit. WOC @ 1145 hrs. MST, 6-18-80.
- Nippled up 5000 psi BOP stack and choke manifold.
- Ran 7-7/8" bit to 4220' after WOC 31 hours and tested casing to 1500

17, 0 520 to 4220 digital	er woo or hours and tested casing	to 1500 psi.
18. I hereby certify that the information above is true and comp	plete to the boot of my knowledge and belief. Drilling Superintendent	December 18, 1980
CONDITIONS OF APPROVAL, IF ANY:	TITLE	DET 1980