

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.E.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> WELL CAR <input type="checkbox"/> WELL OTHER- <u>BRINE</u>		7. Unit Agreement Name
2. Name of Operator <u>WASSERHUND, INC</u>		8. Farm or Lease Name <u>EIDSON STATE</u>
3. Address of Operator <u>1613 SOUTH LOVE STREET, LOVINGTON, N.M. 88260</u>		9. Well No. <u>1</u>
4. Location of Well UNIT LETTER <u>M</u> <u>567.4</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>161.7</u> FEET FROM THE <u>WEST</u> LINE. SECTION <u>31</u> TOWNSHIP <u>16 S</u> RANGE <u>35 E</u> NMPM.		10. Field and Pool, or Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)		12. County <u>LEA</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <u>DRILLED FOR SALT</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-7/8" HOLE  
COMMENCED ROTARY DRILLING 21AUG80 - COMPLETED ROTARY DRILLING 23AUG80  
SET 35.80' 13-3/8" SURFACE CASING - RAN 50 JTS 7" 32# & 35# USED  
TESTED CASING SET AT 1895.0' - CEMENTED WITH 265 SKS CLASS "C"  
CEMENT, 570 SXS HALLIBURTON LIGHT CEMENT CONTAINING 4560# SALT MIXED  
8# W/570, 142# FLOCELE MIXED 1/4# W/570, AND 5SKS CAOL MIXED 2% W/265 -  
PLUGGED DOWN AT 5:30 PM 23AUG80 - CIRCULATED ABOVE CEMENT FROM TOTAL  
DEPTH TO SURFACE - LET CEMENT SET 48 HRS - REQUIRED REVERSE UNIT TO  
DRILL OPEN HOLE INTO SALT FORMATION TO A TD OF 2555' - RAN 84 JTS  
2-7/8" 7.9# C-75 DSSHT TESTED USED TUBING TO 2461.0' - COMMENCED  
PUMPING FRESH WATER DOWN 7" CASING AND RETURNING 9.8# PER GALLON  
BRINE THROUGH 2-7/8" TUBING - BRINE BEING PUMPED INTO APPROVED  
LINED OPEN PIT

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

WASSERHUND, INC

SIGNED [Signature] TITLE PRESIDENT DATE 17SEP80

APPROVED BY [Signature] TITLE Dir. J. Suge DATE SEP 18 1980

CONDITIONS OF APPROVAL: IF ANY