

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-4800	

## SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
(SEE MARKETING FOR PERMIT LIT. FORM C-101 FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Dorchester Exploration, Inc.		8. Farm or Lease Name Morton Solid State Unit
3. Address of Operator 1100 Midland National Bank Tower, Midland, Texas 79701		9. Well No. 2
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM <u>West</u> THE <u>4</u> LINE, SECTION <u>15S</u> TOWNSHIP <u>34E</u> RANGE <u>4</u> N.M.P.M.		10. Field and Pool, or Wildcat Tres-Papalotes <i>Lea</i>
15. Elevation (Show whether DF, RT, GR, etc.) 4116 GR		11. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well spudded at 1:45 pm on August 20, 1980. Drilled 17-1/2" hole to a depth of 400'. Ran 13-3/8" 48# H-40 surface casing and set same at 404'. Cemented casing with 400 sx CL "C" cement and circulated to surface. Tested cement for 30 minutes with a pressure of 600 lbs. per square inch, held ok. Presently drilling 11" hole.

I, I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rick O'Bannon TITLE Proration Administrator DATE August 25, 1980

APPROVED BY Jerry Sexton TITLE Dist. 1, Sup. DATE 10-20-1980  
CONDITIONS OF APPROVAL, IF ANY: