

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐
2. NAME OF OPERATOR
Amoco Production Company
3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
480' FSL & 1980' FWL, Sec. 28
AT SURFACE: (Unit N, SE/4, SW/4)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
LC-057210
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Federal BI
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Wildcat Strawn
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
28-17-32
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3941.4 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 2-19-81. Perforated 12668'-12672', 12676'-12680' and 12693'-12702' with 2 JSPF. Acidized with 3500 gal. 7-1/2% MS acid. Swab tested three days and recovered no oil or gas. Set a cast iron bridge plug at 12650'. Perforated 12516-12524' and 12536'-12540' with 2 JSPF. Acidized with 2500 gal. 7-1/2% MS acid. Swab tested 2 days and recovered no oil or gas. Set a cast iron bridge plug at 12,300' and capped with 35' of cement. Perforated 11634'-11648' with 4 JSPF. Currently flow testing.

0+4-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Peter W. Chester TITLE Ast. Adm. Analyst DATE 3-12-81

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

PETER W. CHESTER

MAR 19 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side