

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other2. NAME OF OPERATOR
Amoco Production Company3. ADDRESS OF OPERATOR
P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 480' FSL & 1980' FWL, Sec. 28

AT TOP PROD. INTERVAL: (Unit N, SE/4, SW/4)

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

RECEIVED

(NOTE: Report results of multiple completion or zone on Form 9-330.)

DEC 30 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to a TD of 12992' and ran 690' of 23# S-95 5-1/2" casing, 448' of 23# N-80 5-1/2" casing, 5260' of 20# N-80 5-1/2" casing, and 6569' of 17# N-80 5-1/2" casing set at 12967'. Cemented with 1400 SX Halliburton Light with additives, 800 SX Class H cement with additives. Plugged down midnight 12-17-80. Cement did not circulate. Will test casing when completion unit moves in.

0+5-USGS, H 1-Hou 1-Susp 1-LBG 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Benton Green

TITLE

Ast. Ad. Analyst

DATE

12-29-80

APPROVED BY
CONDITIONS OF

PETER W. CHLSTER

TITLE

DATE

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side