

N. M. OIL AND GAS COMMISSION
 DEPARTMENT OF THE INTERIOR
 HOBBS, NEW MEXICO 88240
 GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Chevron U.S.A. Inc.
3. ADDRESS OF OPERATOR
P. O. Box 1660, Midland, TX 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
 AT SURFACE: 50' FWL & 1400' FSL
 AT TOP PROD. INTERVAL:
 AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
 FRACTURE TREAT ☐
 SHOOT OR ACIDIZE ☐
 REPAIR WELL ☐
 PULL OR ALTER CASING ☐
 MULTIPLE COMPLETE ☐
 CHANGE ZONES ☐
 ABANDON* ☐

(other) Spudding, running 8 5/8" & 5 1/2" casing

SUBSEQUENT REPORT OF:

RECEIVED
 SEP 14 1981
 OIL & GAS
 U.S. GEOLOGICAL SURVEY
 ROSWELL, NEW MEXICO

5. FEDERAL ID
Federal LC059576
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
Maljamar (Grayburg) Ut.
8. FARM OR LEASE NAME
Maljamar (Grayburg) Ut.
9. WELL NO.
78
10. FIELD OR WILDCAT NAME
Maljamar (Grayburg)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 3, T-17S, R-32E
12. COUNTY OR PARISH
Lea
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
GL 4168'; DF 4176'; KB 4177'

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. This well was spudded @ 1:00 PM on July 6, 1981.
2. The 8 5/8" casing (24#, K-55, ST&C) was landed at 370 (in 12 1/4" hole) and cemented with 450 sacks Class "C" (Yld. 1.32 & Wgt 14.8 P.P.G.) w/2% CACL. Circulate 150 sacks to surface. Work completed on July 8, 1981.
3. The 5 1/2" casing (14#, K-55, ST&C) was landed at 4300' (in 7 7/8" hole) and cemented with 775 sacks "Lite" (Yld. 2.02 & Wgt 14.8 P.P.G.) and 250 sacks Class "C" (Yld. 1.32 & 14.8 P.P.G.) Did not circulate cement to surface. Work completed on July 17, 1981. On July 24, 1981, 250 sacks of Class "C" Cement (Yld. 1.32 & 14.8 P.P.G.) down 8 5/8" x 5 1/2" annulus and fill to surface.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED R. A. Chapman TITLE Engr. Tech. DATE September 11, 1981

APPROVED BY ROGER A. CHAPMAN (This space for Federal or State office use)
 CONDITIONS OF APPROVAL SEP 17 1981

U.S. GEOLOGICAL SURVEY
 ROSWELL, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

SEP 21 1981