

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒

GAS WELL ☐

OTHER ☐

Name of Operator

Arrowhead Oil Corporation

Address of Operator

P. O. Box 548, Artesia, New Mexico 88210

Location of Well

UNIT LETTER D 990 FEET FROM THE North LINE AND 330 FEET FROM

THE West LINE, SECTION 32 TOWNSHIP 17-S RANGE 32-E N.M.P.M.

11. Elevation (Show whether DF, RT, GR, etc.)

5a. Indicate Type of Lease

State ☒

Fee ☐

5. State Oil & Gas Lease No.

B-4109

7. Unit Agreement Date

8. Term of Lease Date

Hover State

9. Well No.

#2

10. Field and Pool, or Whichever

Maliamar

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOBS ☒

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well at 6:00 PM on March 12, 1981. Ran 23 joints of 8 5/8" 24# casing and set at 905' KB. Cemented with 200 sacks of Class C 2% CaCl cement and circulated. Pressure tested to 500# and held for 30 minutes. Test OK. Waited on cement 18 hours and drilled to T.D. with 7 7/8" bit.

Ran 4168' of 4 1/2" 11.6# J-55 casing with DV Tool set @ 2114'. Cemented with 650 sacks of Class C with 50/50 Poz Mix, 2% Gel, 6# Salt and .3 of 1% CFR2. Opened DV Tool and circulated.

Pumped 600 sacks of Halliburton Lite with 1/4# FC, 5# Gilsonite and 20# salt and 50 sacks Class C 2% CaCl thru DV Tool.

Drilled out cement and DV Tool. Tested casing to 1000# psi with no pressure loss.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Shirley A. Loyd*

TITLE Production Clerk

DATE April 15, 1981

Orig. Signed by

Jerry Sexton

APPROVED BY

Diet J. Supp

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: