

C. T. McLAUGHLIN
State 'C' No. 1
1980' FNL & 1980' FEL
Spud 6/18/50.
Set 8 5/8" csg in 10" hole @ 1409'. Cmt w/100 sx.
Set 5 1/2" csg in 7" hole @ 4108'. Cmt w/100 sx.
Drld out to 4385'. Shot OH.
P&A 1/10/52.
Cmt plug 4358-4100'.
Cmt plug 3460-3420'.
Pld 3440' 5 1/2" csg.
Cmt plug 1425-1405'.
Pld 975' 8 5/8" csg.
Cmt @ surf. Mud between plugs.

C. T. McLAUGHLIN
State 'A' No. 2
660' FNL & 1980' FWL
Spud 9/26/43.
15" hole. Set 12 1/2" csg @ 240'. Cmt w/25 sx.
10 3/4" hole. Set 8 5/8" csg @ 1286'. Cmt w/50 sx.
7" hole. Set 5 1/2" csg @ 4120'. Cmt w/100 sx.
TD 4345'. Shot OH.
100' cmt plug 4000-3900'.
Cmt plug 3500-3050'.
Rec 2000' - 5 1/2" csg.
50 sx plug across cut off.
Tagged TOC @ 1800'. Btm @ 2150'.
Spotted plug @ 1331'. Tagged @ 1180'.
Perf @ 350'. Sqz w/120 sx.
Spotted 10 sx @ surf.

LYNX PETROLEUM CONSULTANTS, INC.
State 'BD' No. 1
1980' FNL & 660' FEL
Spud 3/31/59.
12 1/4" hole. 8 5/8" csg set @ 360'. Cmt w/360 sx. Circ.
7 7/8" hole. Set 5 1/2" csg @ 4468'. Cmt w/600 sx. TOC @ 2290'.
Perfs 4213-4362'.
Current producer.

RECEIVED

OCT 18 1985

2000
HOBBS OFFICE