

OIL CONSERVATION DIVISION

P. O. BOX 208R
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
OG-4765	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☒ GAS ☐ OTHER ☐		7. Unit Agreement Name	
2. Name of Operator		6. Firm or Lease Name	
Blanks Energy Corporation		Pennzoil State	
3. Address of Operator		9. Well No.	
600 Blanks Building, Midland, TX 79701		3	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER <u>BC</u> 1830 FEET FROM THE West LINE AND 660 FEET FROM		NE Lovington Penn	
THE North 18 LINE, SECTION 16-South RANGE 37-East			
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
3851' GR 3866' DF		Lea	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL UP ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1503.

- 4-18-81 Spudded 17½ hole @ 6:30 P. M.
- 4-20-81 Ran 10 Jts 13 3/8", 48#, H-40 ST&C (405.81'). Set @ 410' RKB. Cmt'd w/450 sx Class "C" w/2% CaCl₂. Circ cmt'd. WOC 13 hrs. Temp of cmt when mixed 80°F. Tested csg to 600# for 30 min.
- 4-28-81 Ran 105 Jts 8 5/8" 24 & 32# K-55 ST&C (53 jts 24#, 52 jts 32#-4335') w/3 centr & lfs. Set @ 4300'RKB. Cmt'd w/750 sx Howco Lite w/15# salt/sk & ¼# Flocel/sk, tailed in w/250 sx class "H" neat. WOC 11 hrs. Temp of cmt when mixed 80°F. Test csg @ 2500# for 30 min.
- 5-28-81 Ran 297 Jts 4½", 11.6# N-80 (11485'RKB) w/ FS & GS, 10 centr @ 80' intervals. Cmt'd w/650 sx Howco Lite followed by 450 sx Class "H". TOC 6530' (temp sur.). WOC 24 hrs temp of cmt'd when mixed 80°F. Tested csg to 2300# for 30 min.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jim Leudeau TITLE Engineer DATE 6-2-81

Orig. Signed by
John Sexton

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JUN 15 1961