

N.O. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Tenneco Oil Company
3. Address of Operator 6800 Park Ten Boulevard, Suite 200 North, San Antonio, Texas 78213
4. Location of Well UNIT LETTER <u>H K</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>1480</u> FEET FROM THE <u>West</u> LINE, SECTION <u>30</u> TOWNSHIP <u>16S</u> RANGE <u>34E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) GL 4143.1

7. Unit Agreement Name
8. Farm or Lease Name State 1E-30
9. Well No. #2
10. Field and Pool, or Wildcat S. Kemnitz Atoka Morrow
12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/22/81 Spud well.
6/23/81 Ran 9 joints 13 3/8", 54.5#, K55, 8rd STC casing at 391'. Cemented with 375 sxs. C1. "C" +2% CaCl₂. Did not circ. Pump 500 sxs C1 "C" down 13 3/8 x 20 annulas with 1". Had cement returns. Calc top of cement is surface. Pumped plug down with 56 bbls. mud. Plug down at 9:47 a.m. with 250 psi. W.O.C. 15 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Quita Gray</u>	TITLE <u>Production Analyst</u>	DATE <u>June 24, 1981</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dr. L. Gray</u>	DATE <u>JUL 1 1981</u>
CONDITIONS OF APPROVAL, IF ANY:		