

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

NO. BY OFFICE RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. Mine Oil & Gas Lease No.
16800-4

1. TYPE OF WELL		OIL WELL ☐		GAS WELL ☒		DRY ☐		OTHER ☐	
2. TYPE OF COMPLETION		NEW WELL ☒		WORK OVER ☐		DEEPEN ☐		PLUG BACK ☐	
3. Name of Operator		Kimhark Oil & Gas Company		4. Address of Operator		1580 Lincoln St. #700 Denver, CO 80203		5. Well No.	
6. Location of Well		UNIT LETTER <u>N</u>		LOCATED <u>3350</u>		FEET FROM THE <u>South</u>		LINE AND <u>2310</u>	
7. County		Lea		8. Farm or Lease Name		New Mexico State Com		9. Field and Pool, or Wildcat	
10. Date Spudded		12/7/81		11. Date T.D. Reached		2/21/82		12. Date Compl. (Ready to Prod.)	
13. Total Depth		13,325		14. Plug Back T.D.		13,281		15. Elevations (DF, REB, RT, GK, etc.)	
16. Producing interval(s), of this completion - Top, Bottom, Name		13,100-13,199 Devonian		17. Multiple Compl., How Many		N/A		18. Intervals Drilled By	
19. Was Directional Survey Made		Yes		20. Was Well Cored		No		21. Type Electric and Other Logs Run	
DIL-MSFL, CNL/EDC/GR		22. CASING RECORD (Report all strings set in well)		23. LINER RECORD		24. TUBING RECORD		25. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.	
Casing Size		Weight LB./FT.		Depth Set		Hole Size		Cementing Record	
13-3/8"		54.5#		364		17 1/2"		375sx Class G w/2% CaCl	
8-5/8"		32		4565		12 1/2"		132 sx Lite, 200sx Class "G"	
5 1/2"		17 & 20		13,324		7-7/8"		2100sx Class "H" 50/50poz	
Size		TCP		Bottom		Sacks Cement		Screen	
								2-7/8"	
13,100-13,136		4" csg gun 1JSPF		13,181-13,199		4" csg gun 1 JSPF		4500 gal 15% HCl w/ demulsifier w/45,000 SCF N2 & 40 7/8" ball sealers	
4/19/82		24		20/64		175		750	
300		0		Calculated 24-Hour Rate		Oil - Bbl.		Gas - MCF	
WO Sales line		Test witnessed By		Thomas G. Foster		DATE		4/28/82	
DSTs 1,2,3,4,5,7,8		SIGNED		TITLE		DATE			
I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.									

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1782	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1900	T. Strawn 11,266	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 11,422	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2970	T. Miss 12,252	T. Cliff House	T. Leadville
T. 7 Rivers 3146	T. Devonian 13,075	T. Menefee	T. Madison
T. Queen 3817	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 4220	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4538	T. Simpson	T. Gallup	T. Ignacio Ortiz
T. Glorieta 6122	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb 7276	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo 8008	T. Bone Springs	T. Wingate	T.
T. Wolfcamp 9572	T.	T. Chinle	T.
T. Penn. 10585	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 13,075 to 13,200	No. 4, from to
No. 2, from to	No. 5, from to
No. 3, from to	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from N/A to	feet
No. 2, from to	feet
No. 3, from to	feet
No. 4, from to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1782	1900	118	Anhydrite, Sh	11266	11422	156	Lime
1900	2970	1070	Salt, Anhydrite	11422	12252	830	Lime, sd, sh, chert
2970	3146	176	Sand, salt, Anhydrite	12252	13075	823	Lime, sh
3146	3817	671	Anhydrite, Dolomite, sh, salt	13075	TD	250	Dolomite, lime
3817	4220	403	Sd, sh, Dolomite				
4220	4538	318	Dolomite, Anhydrite, sh				
4538	6122	1584	Dolomite, Anhydrite, sh				
6122	7276	1154	Sd, sh, Dolomite				
7276	8008	732	Sd, Dolomite, sh				
8008	9572	1564	Sh, limestone, Dolomite				
9572	10585	1013	Dolomite, lime, sh, chert				
10585	11266	681	Lime, sh				

RECEIVED

MAY 3 1982

O.C.D.
HOBBS OFFICE