

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	2263 Est	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	3233 Est	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	3250 Est	T. Atoka	11900	T. Penn. "D"
T. Yates	3250 Est	T. Miss	13130	T. Leadville
T. 7 Rivers	4092 Est	T. Devonian	14020	T. Madison
T. Queen	4546	T. Silurian		T. Elbert
T. Grayburg	4911	T. Montoya		T. McCracken
T. San Andres	6600	T. Simpson		T. Ignacio Qizte
T. Glorieta		T. McKee	Base Greenhorn	T. Granite
T. Paddock		T. Ellenburger	T. Dakota	
T. Blinberry	7708	T. Gr. Wash	T. Morrison	
T. Tubb		T. Granite	T. Todilto	
T. Drinkard	8460	T. Delaware Sand	T. Entrada	
T. Abo	9390	T. Bone Springs	T. Wingate	
T. Wolfcamp	10600		T. Chinle	
T. Penn.			T. Permian	
T. Cisco (Bough C)			T. Penn. "A"	

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
No. 2, from.....to.....feet.....
No. 3, from.....to.....feet.....
No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
				8200	10060	1860	Dolomite
				10060	11300	1240	Lmstn w/ interbedded shale
				11300	12060	760	Lmstn
				12060	12300	240	Sndstn w/ interbedded shale & lmstn
				12300	12920	620	Lmstn
				12920	13120	200	Sh w/ interbedded Lmstn
				13120	13920	800	Lmstn
				13920	14020	100	Shale
				14020	14089	69	Dolomite