

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator MARATHON OIL COMPANY	8. Farm or Lease Name Anderson Carter
3. Address of Operator P. O. Box 2409 Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>23</u> TOWNSHIP <u>16S</u> RANGE <u>38E</u> N.M.P.M.	10. Field and Pool, or WHDCat Undesignated
11. Elevation (Show whether DF, RT, GR, etc.) G. L. 3692.3	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-17-82 Ran 9 5/8" 36# & 40# K-55-LT&C Casing to 4299'.
Cemented with 1410 sx. 65/35 poz-mix, 6 % D-20 + 10# D-44 + 1/4# D-29 + 5# D-42.
Tailed in with 300 sx Cl. "C" + 10# D-44. Circulated cement to surface.

2-18-82 WOC

2-19-82 Test casing to 2000 psi. Drilled shoe tested formation 11.0 ppg EMW.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eric M. Pingle TITLE Production Engineer DATE 3-5-82

ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPR. DATE 8 1982

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAR -8 1982

O.C.D.
HODS OFFICE