## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

TOT LAND THE TELE OF		
we. of Capits Acceives		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.	$\mathbf{I}$	
LAND OFFICE		
OPPRATOR		

## OIL CONSERVATION DIVISION

SANTA FE, NEW MEXICO 87501  SUNDAY NOTICE DATE AND API NO. 30-025-277.14  API NO. 30-025-277.14  SUNDAY NOTICE S AND REPORTS ON WELLS  SUNDAY NOTICES AND ANABORD  SUNDAY NOTICES OF INTENTION TO:  SUNDAY NOTICES OF INTENTION TO:  SUBSEQUENT REPORT OF:  SUBSECUENT REPORT OF:  SUBSECU							
SANTA FE, NEW MEXICO 87501    Substitution   Simulation   Solution   Special   Solution   Special   Solution   Special   Speci	POITUBIRTEID		P. O. BO	X 2088		Form C-103	
API No. 30-025-27734	SANTA FE		SANTA FE, NEV	V MEXICO 87501		Kevised 10-1-;	
API No. 30-025-27734	FILE				La Indiagte Tv	ne of Leane	
API No. 30-025-27734  API No. 30-025-27734  SUNDRY NOTICES AND REPORTS ON WELLS  SUNDRY NOTICES AND REPORTS ON WELLS  TO SUNDRY NOTICES AND REPORTS ON WELLS  SUNDRY NOTICES AND REPORTS ON WELLS  TO SUNDRY NOTICES AND REPORTS A	U.S.G.S.				·		
API No. 30-025-27734  SUNDRY NOTICES AND REPORTS ON WELLS  OFFICE STATES OF THE TOTAL TOTA	LAND OFFICE				State [X]	Fee	
SUNDRY NOTICES AND REPORTS ON WELLS  ONLY WILL OTHER.  ONLY WELL OTHER.  OTHER WELL  OTHER  O	OPERATOR					Gas Lease No.	
SUNDRY NOTICES AND REPORTS ON WELLS  OF SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS  OF SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS  OF SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS  OF SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS  OF SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS  OF SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS AND REPORTS ON WELLS AND RESERVE AND SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS AND SET IN THE SUMPLY NOTICES AND REPORTS ON WELLS AND SET IN THE SUMPLY NOTICES AND REPORTS ON A STREET AND SET IN THE SUMPLY NOTICE OF INTENTION TO:  OF SET IN THE SUMPLY NOTICE OF INTENTION T		AP	I No. $30-025-2773$	44	B-3610		
Total Depth  Manager Flans  Manager					mmm	TITITITI	
The answer of Constitute Phillips Petroleum Company  #### Of Dentrol Phillips Petroleum Company  ###################################	(DO NOT USE THIS FORM	FOR PROPOSALS TO	DRILL OR TO DEEPEN ON PLUG	BACK TO A DIFFERENT RESERVOIR.			
Total Depth  Millips Petroleum Company  Phillips Petroleum Company  Mexco-A  4001 Penbrook, Odessa, TX 79762  8  Scallen al Well  D . 660	032 4	CPPCICATION FOR PEN	MIT = TPORM C-1017 FOR SC	CH PROPOSACS.)	7 154 45555	777777777777777777777777777777777777777	
Phillips Petroleum Company  Phillips Petroleum Company  Mexco-A  Outperlow  Autority Phillips  Phillips Petroleum Company  Mexco-A  Outperlow  Autority Phillips  Botton of Weil  Outperlow  Centrolly Phillips  Botton of Weil  Outperlow  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  CHECK Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  CHECK Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  CHECK Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  CHECK Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  CHECK PLANT  OTHER  CHECK PLANT  Interior Complete Comp					7. Omit Agreem	ent None	
Mexco-A  3. Well No.  4001 Penbrook, Odessa, TX 79762  8. Bases of Operation  4001 Penbrook, Odessa, TX 79762  8. Bases of Operation of Well  10. 660		OTHER-					
### ADOI Penbrook, Odessa, TX 79762  #### ADOI Penbrook, Odessa, TX 79762  #### ADOI Penbrook, Odessa, TX 79762  #### ADOI Penbrook, Odessa, TX 79762  ##### ADOI Penbrook, Odessa, TX 79762  ###################################	·	·			8. Farm or Lea	8. Farm or Lease Name	
4001 Penbrook, Odessa, TX 79762  Scention of Weil  Out Victors D . 660 recryson the north the AMS 660 recryson the AMS 12. County Maljamar Gb/SA  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data Subsequent Report of:  Subsequent Report of Complete Of Intention to:  ALMERIA AMS Subsequent Report of:  ALMERIA AMS 67 recryson the AMS 660 recryson the AMS 660 recryson to the Data Subsequent Report of:  ALMERIA AMS 67 recryson the AMS 660 recr	Phillips Peti	Phillips Petroleum Company			Mexco-A	Mexco-A	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  COMMENSE CASING  CHANGE PLANS	dress of Operator				9. Well No.	· · · · · · · · · · · · · · · · · · ·	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  CHARGE PLANS  COMMITTEE AND CEMEUR JOB  PLUS AND ABANDOMLE PLANS  COMMITTEE AND CEMEUR JOB  COMMITTEE AND CEMEUR JOB	4001 Penbrook	k, Odessa, T	X 79762		l 8.		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  **REMARK PLANS***  CHARGE PLANS***  TOWARD PRANCE**  **REMARK PLANS***  TOWARD PRANCE**  **REMARK PLANS***  CHARGE PLANS***  CHARGE PLANS***  TOWARD CANDAMADON**  CHARGE PLANS**  TOWARD DESCRIPTION OF CHARGE PLANS**  TOWARD DESCRIPTION OF CHARGE PLANS**  TOWARD PLANS AND CEMENT AND C	ocation of Well			· · · · · · · · · · · · · · · · · · ·		Pool or Wildow	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  CHANGE FLANS  ALTERING CASING  FLUC AND ADMONDIAGE FLANS  CHANGE FLANS  COUNTRICE  FLUC AND ADMONDIAGE FLANS  CHANGE FLANS  CHANGE FLANS  ALTERING CASING  FLUC AND ADMONDIAGE FLANS  CHANGE					1 16 1 .	=	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  ALTERING CABING  CHANGE PLANS  COMMENCE OF PLUE AND ASAMDON  P	UNIT LETTERD	660	PEET FROM THE north	LINE AND <u>660</u> FE	EET FROM MAIJAMA	Maljamar Gb/SA	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  PLUE AND ADADOOM COMMERCE OFFICIAL WORK OFFICE ALLE ! 103.  MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82. Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C". 2% CaCl, 1/4#/sx celloflake. Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WCC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Drlg.  TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, IT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller  **THE Senior Engineering Specialist save May 26, 1982							
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  ALTERING CABINE  COMMENCE OF INTENTION TO:  SUBSEQUENT REPORT OF:  ALTERING CABINE  COMMENCE OF INTENTION TO:  SUBSEQUENT REPORT OF:  ALTERING CABINE  COMMENCE OF INTENTION TO:  SUBSEQUENT REPORT OF:  ALTERING CABINE  COMMENCE OF INTENTION TO:  ALTERING	THE West	E. SECTION 1	TOWNSHIP 17-S	#ANCE 32-E	1111111		
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  SUBSEQUENT		-, <del></del>		NAME			
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  SUBSEQUENT REPOR	mmmm	MIIIII	15. Elevation (Show whether	DF, RT, GR, etc.)	12. County	<del>,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,</del>	
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  SUBSEQUENT REPOR	///////////////////////////////////////	VIIIIIII	•				
SUBSEQUENT REPORT OF:  SUBSEQUENT REPORT OF:  REMEDIAL WORK  COMMERCE DAILLING DAYS.  CHANGE PLANS  TOTAL Depth		7777777X	<del> </del>				
NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:  TOTAL PLOTE ASSING  PLUE AND ABANDON CHARGE PLANS  CONSIDER TEST AND CEMENT JOS X  TOTAL Depth  TOTA	C	heck Appropria	ate Box To Indicate 1	Nature of Notice, Report	or Other Data		
Total Depth  Total						F:	
Commence prize casine  Change Plans  Total Depth  Total Dept	•					•	
Commence prime and alter casine commence of the proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed out of the proposed of Completed Operations (Clearly state all pertinent dates).  MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82.  Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Drlg.  3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. Wilh w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller **ITRE Senior Engineering Specialist **OATK May 26, 1982*					<u>г</u>	_	
CASING TEST AND CEMENT JOB TOTAL Depth  OTHER  CHANGE PLANS  OTHER  TOTAL Depth  Total Case, including estimated date of starting any proposed  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Case, 352'.  Total Case, 352'.  Woll As 3-13-82.  Total Case, 352'.  Total Ca	=		PEGE AND ABANDON		壽	<b>=</b>	
Total Depth  Total	PORARILY ABAHDON		C		<del> </del>	AND ABAHDONMENT	
Prescribe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or Complete 195.  3-13,14-82:  MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82.  Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  Drlg.  3-15 thru 23-82:  Drlg.  TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller  Title Senior Engineering Specialist care May 26, 1982	OR ALTER CASING	-	CHANGE PLANS	CASING TEST AND CEMENT JOB	X		
Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed or (N) SEE NULE 1763.  3-13,14-82:  MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82.  Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82:  Drlg.  TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  3-25-82:  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982				OTHER	Total De	epth X	
MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82.  Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  Drlg.  3-15 thru 23-82:  Dr 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller  W. J. Mueller  TITLE Senior Engineering Specialist May 26, 1982	THER			ł			
MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82.  Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC  8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd  csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength  of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Drlg.  3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to  surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd  w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal  followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  Quip: Series 900, 3000# WP, double, w/l set pipe rams, 1 set blind rams, manually operated,  he/obs/cer/ity that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist CALL May 26, 1982							
MI and RV Cactus Drlg rig. Spudded 12-1/4" hole @ 11:45 AM 3-13-82.  Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'.  Western Co. cmtd w/350 sx Class "C", 2% Cacl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC  8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test Tstd  csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength  of cmt test 500#+. Time cmt in place prior to test 12 hrs.  Drlg.  3-15 thru 23-82:  TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to  surface. WIH w/DP and DC's to circ.  3-25-82:  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd  w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal  followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  Guips Series 900, 3000# WP, double, w/1 set pipe rams, 1 set blind rams, manually operated,  he/sbycerity that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist May 26, 1982	Describe Proposed or Comp	ieted Operations (C	learly state all pertinent det	ails, and give pertinent dates, is	ncluding estimated date of	starting any proposed	
Drld 352' and circ 1/2 hr. COOH. Set 8-5/8" 24#, K-55, ST&C csg @ 352'. Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake. Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Drlg.  3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Quip's Series 900, 3000# WP, double, w/1 set pipe rams, 1 set blind rams, manually operated.  The objectify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller Senior Engineering Specialist Care May 26, 1982	•						
Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82:  Drlg.  3-24-82:  TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  Quipt Series 900, 3000# WP, double, w/1 set pipe rams, 1 set blind rams, manually operated.  heads before the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  W. J. Mueller  Title Senior Engineering Specialist of the late of	3-13,14-82:						
Western Co. cmtd w/350 sx Class "C", 2% CaCl, 1/4#/sx celloflake. Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82:  Drlg.  3-24-82:  TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  Series 900, 3000# WP, double, w/1 set pipe rams, 1 set blind rams, manually operated.  Prep to complete is true and complete to the best of my knowledge and belief.  W. J. Mueller  W. J. Mueller  TILL Senior Engineering Specialist Outcome May 26, 1982		Drld 352' a	and circ 1/2 hr.	COOH. Set 8-5/8" 2	24#, K-55, ST&C	csg @ 3521.	
Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. Circd 80 sx. WOC 8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Drig.  3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  Displaced w/20 BFW. Max press 250#, Bmpd plug w/750#. WOC 12 hrs before test Tstd csg to Circ 85 sx cmt.  Prep to complete.  W. J. Mueller  Title Senior Engineering Specialist Date May 26, 1982		Western Co	<ul> <li>cmtd w/350 sx C</li> </ul>	lass "C", 2% CaCl, 1	/4#/sx celloflal	ke.	
8 hrs, cut off csg, welded on head and NU BOP's. WOC 12 hrs before test. Tstd csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Dr1g.  3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Guip: Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  Defety kertly that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  Title Senior Engineering Specialist Date May 26, 1982		Displaced v	w/20 BFW. Max nr	ess 250# Rmpd plug	7750# Circl !	SO on MOC	
csg to 600#, OK. Temp of cmt 65°, temp in formation 62°. Estimated strength of cmt test 500#+. Time cmt in place prior to test 12 hrs.  3-15 thru 23-82: Drlg.  3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Quipt Series 900, 3000# WP, double, w/l set pipe rams, 1 set blind rams, manually operated.  The followed by 500 sx Class "C" w/nowledge and belief.  W. J. Mueller virte Senior Engineering Specialist OATE May 26, 1982		8 hre cut o	officer wolded on h	and and NII BOD!		OU DA. WUU	
of cmt test 500#+. Time cmt in place prior to test 12 hrs.  Dr1g. 3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Quips Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  Applied Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  W. J. Mueller Tirus Senior Engineering Specialist May 26, 1982	•						
3-15 thru 23-82: Drlg. 3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ. 3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Quipa Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. Will w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller Tiret Senior Engineering Specialist OATE May 26, 1982		csg to 600#	, UK. Temp of cmt	oo, temp in formatio	n 62°. Estimato	ed strength	
3-15 thru 23-82: Drlg. 3-24-82: TD 4564'. Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. WIH w/DP and DC's to circ. 3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Quipa Series 900, 3000# WP, double, w/l set pipe rams, 1 set blind rams, manually operated.  Dresser/Atlas ran DLL, RXO, GR/Cal, CN-GR/Cal from 2000' to surface. With w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  W. J. Mueller Tiret Senior Engineering Specialist OATE May 26, 1982		of cmt test	t 500#+. Time cm	t in place prior to	test 12 hrs.		
surface. WIH w/DP and DC's to circ.  3-25-82: Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Quip Series 900, 3000# WP, double, w/l set pipe rams, 1 set blind rams, manually operated.  hereby certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller Tirle Senior Engineering Specialist May 26, 1982	3-15 thru 23-82:	Drlg.		_			
surface. WIH w/DP and DC's to circ.  Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557". Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Prep to complete.  Series 900, 3000# WP, double, w/l set pipe rams, 1 set blind rams, manually operated.  he/eby.cerilly that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  Title Senior Engineering Specialist May 26, 1982					N-GR/Cal from 20	000' to	
Set 111 jts 4-1/2", 11.60#, N-80, LT&C csg @ 4557'. Western Co. cmtd w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt. Prep to complete.  Prep to complete.  Series 900, 3000# WP, double, w/1 set pipe rams, 1 set blind rams, manually operated.  The best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982		surface. V	WIH w/DP and DC's	to circ.	,		
w/600 sx TLW, 10% DD, 10#/sx salt, 3#/sx Gilsonite, 1/4#/sx celloseal followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  Quips Series 900, 3000# WP, double, w/l set pipe rams, 1 set blind rams, manually operated.  hereby certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982	3-25-82				57! !! 0		
followed by 500 sx Class "C" w/1/4#/sx celloseal. Circd 85 sx cmt.  Prep to complete.  Quip: Series 900, 3000# WP, double, w/1 set pipe rams, 1 set blind rams, manually operated.  The last of the local structure and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist OATE May 26, 1982	, =, 02.	/600 m	100 mm 1041	n-ou, mrac csg (4)	western Co	J. CMEA	
Prep to complete.  Quip: Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  The by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982		w/out sx Tl	LW, 10% DD, 10#/S	x salt, 3#/sx Gilson	ite, 1/4#/sx cel	lloseal	
Quips Series 900, 3000# WP, double, w/l set pipe rams, l set blind rams, manually operated.  hereby certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982				' w/1/4#/sx cellosea	.1. Circd 85 sx	cmt.	
he by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982		Prep to con	mplete.				
he by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982							
he by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982							
he by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982							
hereby certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982							
he by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982							
he by certify that the information above is true and complete to the best of my knowledge and belief.  W. J. Mueller  TITLE Senior Engineering Specialist DATE May 26, 1982	uipa Series 900	3000# WP	double, w/l cet ;	nine rame. 1 cet hli	nd rame manual	ly operated	
Mikuller W. J. Mueller Senior Engineering Specialist May 26, 1982	- /	rmation above is tru	e and complete to the best	of my knowledge and belief.	ria ramo, manual.	ry obstaced.	
	1 1 1		prese id tub bd#t (	, recovered to the second of the second o			
	A DIA Illa						
	Muller	W. J. N	Mueller Title Ser	nior Engineering Spe	cialist OATE May	26, 1982	
		Alternative Administration					
						w i 1982 -	