

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240  
DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210  
DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-27738
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. V-148
7. Lease Name or Unit Agreement Name Treasure TE State
8. Well No. 1
9. Pool name or Wildcat Northeast Lovington Penn

Section 24	Township 16S	Range 36E	NMPM	Lea	County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3856' GR					

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☐ GAS WELL ☐ OTHER P&A

2. Name of Operator  
YATES PETROLEUM CORPORATION

3. Address of Operator  
105 South 4th St., Artesia, NM 88210

4. Well Location  
Unit Letter A : 510 Feet From The North Line and 550 Feet From The East Line

Section 24 Township 16S Range 36E NMPM Lea County

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to P&A well as follows:

Set CIBP at 11100' w/35' cement on top & set CIBP at 10150' w/35' cement on top.

Spot 50 sx cement plug 50' in and 50' out casing stub.

Pull up to 6350' and spot 60 sx cement plug 6350-6250'.

Pull up to 4925' and spot 50 sx cement plug 4925-4825'.

Pull up to 4300' and spot 80 sx cement plug 4300-4200'.

Pull up to 2135' and spot 30 sx cement plug 2135-2035'.

Pull up to 40' and spot 10 sx surface plug.

Set regulation abandonment marker.

Will pump fresh water ahead of cement and 2 bbls fresh water followed by mud behind cement plugs. Will add CaCl2 as necessary to accelerate setting time. Cement properties: Class "C" 14.8 ppg, 6.3 gwps, 1.32 cfps.

NOTIFY NMOC, HOBBS, NM 24 HOURS PRIOR TO PLUGGING.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Juanita Goodlett TITLE Production Supervisor DATE 1-29-93

TYPE OR PRINT NAME Juanita Goodlett TELEPHONE NO. 505/748-1471

(This space for State Use)  
ORIGINAL SIGNED BY JERRY SEXTON  
SUPERVISOR

FEB 03 1993

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
FEB 9 1993  
FBI - NEW YORK