

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Yates Petroleum Corporation
Address of Operator
207 South 4th St., Artesia, NM 88210
Location of Well

UNIT LETTER A 510 FEET FROM THE North LINE AND 660 FEET FROM
THE East LINE, SECTION 24 TOWNSHIP 16S RANGE 36E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)
3856' GR

5a. Indicate Type of Lease
State ☒ For ☐

5. State Oil & Gas Lease No.
V-148

7. Unit Agreement Name

8. Farm or Lease Name
Treasure TE State

9. Well No.
1

10. Field and Pool, or Wildcat
Northeast Lovington Penn

12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Perforate & Treat ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 11500'. Pulled rods & tubing. Acidized well w/3000 gal 15% gel NE acid & 2% KCL. WIH & perforated 17 .50" holes as follows: 10652-655' & 10657-60' (1 SPF - 8 holes); 10771-775' & 10781-784' (1 SPF - 9 holes). Acidized perfs 10652-10784' w/2500 gal 15% NE acid & N₂. WIH & perforated 10375-382' w/14 .50" holes (2 SPF). Acidized perfs 10375-382' w/1500 gal 15% NE acid & N₂ plus ball sealers. WIH & perforated 10201-10215' w/24 .50 holes as follows: 10201-204' & 10206-215' (2 SPF). Ran packer & set at 10127, set RBP at 10300'. Acidized perfs 10201-215' w/2500 gal 15% NE acid & N₂. RBP set at 11240', unable to move after perforating 11278-310' due to junk in hole. PBD 11240'.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ernesta Doolett

TITLE Engineering Secretary

DATE 9-14-82

APPROVED BY Eddie W. Leary

TITLE OIL & GAS INSPECTOR

DATE SEP 20 1982

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

SEP 16 1982

**O.C.D.
HOBBS OFFICE**