

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator C & K PETROLEUM, INC.		5. State Oil & Gas Lease No.
3. Address of Operator P. O. DRAWER 3546, MIDLAND, TEXAS 79702		7. Unit Agreement Name
4. Location of Well UNIT LETTER P 660' FEET FROM THE South LINE AND 660' FEET FROM THE East LINE, SECTION 28 TOWNSHIP 16-S RANGE 37-E NMPM.		8. Farm or Lease Name Shipp "28"
		9. Well No. No. 1
		10. Field and Pool, or Wildcat Casey (Strawn)
15. Elevation (Show whether DF, RT, GR, etc.) 3783'		12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 3-14-82 at 10:30AM.

Drilled 17-1/2" hole to 400'. Set 13-3/8", 48#, H-40, ST&C Csg @ 400'. Cemented with 420 sx Class "C" w/2% CaCl₂ + 1/4# Flocele. Cement circulated to surface. Plug down @ 12:30AM, 3-15-82. WOC 18 hours. Tested csg to 1000 psi for 30 minutes. Held okay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Michael W. Gore TITLE Drilling Superintendent DATE March 16, 1982

ORIGINAL SIGNED BY

JERRY SEXTON

APPROVED BY DISTRICT SUPERVISOR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 19 1982