| DISTRIBUTION EANTA FE PILE | HEW MEXICO OIL CON | REERVATION COMMISSION | Plum U-103 Supercedes Old C-103 and C-103 Elloctive 14-88 |
|---|--|--|--|
| U.S.O.S. LAND OFFICE OPERATOR | | | State X Foa 5. State Oil 6 Gas Lease No. V-304 |
| . VIE "APPLICATION | NOTICES AND REPORTS OF | N WELLS | 7, Unit Agreement Name |
| WELL X WILL . | 07H1A+ | | |
| W.A. Moncrief, Jr. | | 8. Form or Leave Name | |
| 1, Address of Operator | | Dean State | |
| 400 Metro Bldg., Midland, Texas 79701 | | . 1 | |
| 4. Location of Well whit letter C 1980 peet prose the West Line and 660 peet page | | 10. Field and Pool, or Wildcat Dean Devonian | |
| THE north LINE, SEETION | 35 темнение <u>15</u> | S AAHPE 36E HMP | |
| | 15, Elevation (Show whether | | 12. County |
| | 3859 GD, 3874 | | Lea |
| Check Ap | propriete Box To Indicate] ENTION TO: | Nature of Notice, Report or C | Rher Data NT REPORT OF: |
| ERFORM REMEDIAL WORK | 982 Acres 400 ADARDON [| AEMEDIAL WORK | ALTERING CADING |
| Are ou veseu evering Line | SHARRE PLANS | SASING TEST AND CEMENT JOS X | PLUS AND ASANSONMENT (|
| | | | |
| OTHER | | 1 | |
| F. Describe Proposed or Codiploted Operational, SEE HULE 1709. | | | |
| (1.) Operator reached TI (2.) Ran 5½" 20# & 17# 8 up casing 13' off h | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. 15 minutes. Held OK rvey 6-28-82 and found to out and complete from | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |
| (1.) Operator reached TI (2.) Ran 5½" 20章 & 17章 8 up casing 13' off it Class "H" w/½章 Flo HALAD 22-A. P.D. 1 (3.) Tested to 2000章 for (4.) Ran temperature sur (5.) Operator will drill | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. 15 minutes. Held OK rvey 6-28-82 and found to out and complete from | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |
| (1.) Operator reached TI (2.) Ran 5½" 20章 & 17章 8 up casing 13' off it Class "H" w/½章 Flo HALAD 22-A. P.D. 1 (3.) Tested to 2000章 for (4.) Ran temperature sur (5.) Operator will drill | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. 15 minutes. Held OK rvey 6-28-82 and found to out and complete from | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |
| (1.) Operator reached TI (2.) Ran 5½" 20章 & 17章 8 up casing 13' off it Class "H" w/½章 Flo HALAD 22-A. P.D. 1 (3.) Tested to 2000章 for (4.) Ran temperature sur (5.) Operator will drill | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. 15 minutes. Held OK rvey 6-28-82 and found to out and complete from | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |
| (1.) Operator reached TI (2.) Ran 5½" 20章 & 17章 8 up casing 13' off it Class "H" w/½章 Flo HALAD 22-A. P.D. 1 (3.) Tested to 2000章 for (4.) Ran temperature sur (5.) Operator will drill | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. 15 minutes. Held OK rvey 6-28-82 and found to out and complete from | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |
| (1.) Operator reached TI (2.) Ran 5½" 20章 & 17章 8 up casing 13' off it Class "H" w/½章 Flo HALAD 22-A. P.D. 1 (3.) Tested to 2000章 for (4.) Ran temperature sur (5.) Operator will drill | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. The same of the same | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s top cement at 10,040' o m Devonian open hole 13 | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |
| (1.) Operator reached TI (2.) Ran 5½" 20季 & 17季 8 up casing 13' off the Class "H" w/技 Floth HALAD 22-A. P.D. 1 (3.) Tested to 2000季 for (4.) Ran temperature sure (5.) Operator will drill when completion unit | o of 13,731' driller as round & buttress N-8 bottom and cemented @ cel per sack + .5 of 11:45pm 6-27-82. The same of the same | nd 13,714' Welex 6-25-8 0 range 3 casing by cas 13,714' by casing talle 1% CFR-2 + 5# KCL per s top cement at 10,040' o m Devonian open hole 13 | 2. ing talley. Picked y with 1050 sax ack + 6/10 of 1% |