		ANTE CARE LA
	1	
	•	
	Form C+103	
	Supersedex ()14 C-142 and C-101 Ellectivo 1-1-65	
0.1.	Sinto X Fee	
натон	S. State Cil & Gas Lease He. V-304	
SUNDRY NOTICES AND DEPORTS ON WELLS		
SUNDRY NOTICES AND REPORTS ON WELLS	7. Unit Agreen out times	
ALL X WILL OTHER.		
	B. Fumer Lease Hame Dean State	
A. Moncrief, Jr.	9. Well tio.	
0 Metro Bldg, Midland, Texas 79701	L 10. Field and Fool, or Wildcat	
NIT LETTER C 1980 FEET FACE THE WEST LINE AND 660 FEET FA	Dean Devonian	~~~ ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
anth 35 155 36E	illillillillillik	
HE TOULING BLETION TOWNBHIP BARCE HAR	12. County	
3859' GD, 3874' KB	Lea	
Check Appropriate Box To Indicate Nature of Notice, Report or C		
NOTICE OF INTENTION TO: SUBSEQUE	NT REPORT OF:	
AN REWEDIAL WORE	ALTERING CABING Plug and abandowwent	
CAARLEY ABANDAN CAARNE CHANS CAARNE C		
NCA		
evenue Proposed or Completed Operations (Clearly state all perfinent details, and give perfinent dates, includi	ing estimated date of starting any propul	nd a second
) Operator spudded at noon 4-28-82 with Landis Rig #2.		and the second
) Operator spudded at noom +-20-02 with handle hig with	then at 35A' as stated on	
) Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sends or the surfa	ice occured as a result of	
) Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfa the brine water flow anticipated in the salt section. Mr. Jerry S	ice occured as a result of	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfa the brine water flow anticipated in the salt section. Mr. Jerry S change by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 	ice occured as a result of Sexton was advised of this 2058' by casing talley on	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry S change by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Commented w/1283 max lite w/10# gilsonite per sack + 3# per s	ace occured as a result of Sexton was advised of this 2058' by casing talley on arma-chek per sack	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfar the brine water flow anticipated in the salt section. Mr. Jerry S change by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement circulations of the same same same same same same same sam	ace occured as a result of Sexton was advised of this 2058' by casing talley on arma-chek per sack Erculated 45 Sax. Tested	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement ciccasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Sat 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 	ace occured as a result of Sexton was advised of this 2058' by casing talley on erma-chek per sack Irculated 45 Sax. Tested nto lined reserve pits. range 3 ST&C on bottom	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement circasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water ir Set 8-5/8" casin# @ 4898' on 5-10-82 as follows: 604' cf 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested nto lined reserve pits. range 3 ST&C on bottom follows: Halliburton	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement circasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flowed for the same stage w/50 sax class "C" w/5# salt per sack & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt & ½# Flowed for same set followed by 200 sax regular w/5# salt for % followed by 200 sax regular w/5# salt for % followed by 200 sax regular w/5# salt for % followed by 200 sax regular w/5# salt followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular w/5# salt followed by % followed by % followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular w/5# salt followed by % followed by % followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular w/5# salt followed by % followed by 200 sax regular	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested nto lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cal per sack + 5# cal per sack. PD on 1st	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# pe followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cicasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min by rool @ 2979' & circulated for 4 hours. Cemented second stage v 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested nto lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# pe followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cicasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Figilsonite per sack followed by 200 sax regular w/5# salt & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cal per sack + 5# cal per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement circasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage w 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completed for the surface water in the salt water in the salt second stage in the salt water in the salt water in the salt second stage in the salt water in the salt water in the salt with the salt second stage in the salt water in the salt second stage in the salt second stage with the salt water in the salt with the salt water in the salt water i	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Inculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cal per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# pe followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cicasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Figilsonite per sack followed by 200 sax regular w/5# salt & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek. annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Inculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cal per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# pe followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cicasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt by a salt by \$\frac{10}{2}\$ when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cal per sack + 5# cal per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# pe followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cicasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Figilsonite per sack followed by 200 sax regular w/5# salt & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek. annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# pe followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cicasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Figilsonite per sack followed by 200 sax regular w/5# salt & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek. annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 25-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cf casing to 1203# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 25-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# perfollowed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cf. casing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 25-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# perfollowed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cf. casing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 25-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# perfollowed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cf. casing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 25-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# perfollowed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement cf. casing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage v 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had completend of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	
 Operator decided to set 13-3/8" into the Rustler anhydrite rather form C-101 to be sure no contamination of water sands or the surfathe brine water flow anticipated in the salt section. Mr. Jerry Schange by telephone. Set 49 joints (2035.18') of 54.5# J-55 range 3 13-3/8" casing @ 2 5-2-82. Cemented w/1283 sax lite w/10# gilsonite per sack + ½# per followed by 300 sax Class "C" w/2% CaCl. (Western Co.). Cement ciccasing to 1200# for 20 minutes. Held OK. WOC 12 hrs. Encountered salt water flow @ 2670' @ 4pm 5-4-82. Flowed water in Set 8-5/8" casing @ 4898' on 5-10-82 as follows: 604' of 28# S-80 & 4280' of 32# K-55 range 3 ST&C on top. Cemented in 2 stages as cemented first stage w/750 sax Class "C" w/5# salt per sack & ½# Flo stage @ 6:15am 5-9-82. Pressured up on casing to 1600# for 30 min DV tool @ 2979' & circulated for 4 hours. Cemented second stage w 9½# salt & ½# Flo cel per sack followed by 2,000 gallons Flo-chek. annulus to 1050# when cement reached surface & pumped remainder in to 2600# for 15 minutes. Held OK. WOC 18 hrs. Still had complete end of WOC time. 	ace occured as a result of Sector was advised of this 2058' by casing talley on arma-chek per sack Irculated 45 Sax. Tested ato lined reserve pits. range 3 ST&C on bottom follows: Halliburton Flo Cel per sack + 5# cel per sack. PD on 1st nutes. Held OK. Opened w/1600 sax Class "C" w/ . P.D. @ 2pm. Pressured ato formation. Pressured te water shut off at	

. 2