STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

ONSERVATION DIVISION

ENERGY AND WINVERACS DEFAITMENT	OIL CONSERVAT	TION DIVISION			Form C-103 ·	
HO. OF COMICS SECRIVED	P. O. BOX				Revised 10-1-78	
DISTRIBUTION	SANTA FE, NEW					
BANTA FE	SANTA PE, NEW I	MEXICO OFFICE	Г	sa. Indicate Type o	i Leuse	
FILE				State X	F•• 🔲	
U,\$.0.\$.				5. State Oil & Gas		
LAND OFFICE			1			
OPERATOR				V-395 and I	_G-4223	
		vc. 1.6				
SUNDRY	OSALS TO DAILL OR TO DEEPEN OR PLUG BAID FOR PERMIT - FORM C-101) FOR BUCH	NELLS CR TO A DIFFERENT RESERVOIR	. }			
DO NOT USE THIS FORM FOR PROP USE "APPLICATION	DE PERMIT - (FORM C-101) FOR SUCH	PROPOSALS.)		7. Unit Agreement	Name	
1.			İ			
OIL SAB WELL WELL WELL	OTHER-			8. Farm or Lease 1	Name	
2. Name of Operator					Sombrero State	
W.A. Moncrief, Jr.					9. Well No.	
3. Address of Operator					j	
too at the Pldo Midland	d Texas 79701			10. Field and Pool, or Wildcat		
400 Metro Bldg., Midland, Texas 79701 4. Location of Well WHIT LETTER N 660 FEET FROM THE SOUTH LINE AND 1400 FEET FROM					10, Field and Pool, or window	
4. Location of Well	a nuth	1400	FEET FROM	Atoka-Morro	W	
N N	660 FEET FROM THE SOULII	LINE AND	PERI FROM			
U		27.E	·	VIIIIII.		
roet errio	18 TOWNSHIP 16S	RANGE	NMPM.			
THE WEST TINE, SECTION		12. County	444444			
15. Elevation (Show whether DF, RT, GR, etc.)						
	4150.5 Gd.,	4165.5 KB		Lea	7////////	
	7 7 1 1 1 mm N	arms of Notice Repo	er or Oth	er Data		
Tie. Check	Appropriate Box To Indicate N	attile of Notice, Repo	FOLIENT	REPORT OF:		
NOTICE OF IN	TENTION TO:	5003	,,_,			
			$\overline{}$		ING CASING	
[PLUG AND ABANDON X	REMEDIAL WORK	님			
PERFORM REMEDIAL WORK		COMMENCE DRILLING OPNS.		PLUG A	ND ABANDONMENT	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed (1.) Operator set CIBP at 12,891 w/35' cement on top of CIBP. Perforated Atoka sand 12,657-60 and 12,608-15 (12 holes) w/casing gun.

A/1500 gallons 15% HCL and swabbed dry with gas TSTM.

Operator has concluded that the Atoka is non-commercial and proposed to plug as follows:

Circulate hole with mud.

- Spot 100' cement plug from 12,583-12,483 with 2" tbg. (A)
- Pull tubing, free point casing, shoot casing at free point and pull same. (B)
- Run tubing and spot 100' cement plug 50' in and 50' out of 4½" casing stub. (C)
- Spot 100' cement plug in and out of 8-5/8" casing at 4500'. (D)
- (E)

Wildes Wildel					SEP 27 1983
n	E. Sharuton	TITLE	Exploration Manager	DATE_	9-23-83
18. I hereby certify	that the information above is true an	d complete to the be	at of my knowledge and belief.		
	. : : : :	al subsubsubsubsubsubsubsubsubsubsubsubsubs	1		
			4: 57 te +		
(F) (G)	in cement at the sur	tace.	5/8" casing and install	•	

SEP 26 1983
HOSS C.D.
OFFICE