

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-27891

5. Indicate Type of Lease

STATE ☐ FEE ☒ XX

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

Tilley

8. Well No. 1

8. Pool name or Wildcat
Shoebar Devonian and Atoka

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Primero Operating, Inc.

3. Address of Operator

PO Box 1433, Roswell, NM 88202-1433

4. Well Location

Unit Letter N : 330 feet from the South line and 1815 feet from the West line

Section 26

Township 16S Range 35E

NMPM

Lea

County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

3967 gr

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒ XXXX

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Pursuant to plan constructed with Chris Williams, we proposed to plug and abandon this well as follows:

25 sx plug at 11,400'

25 sx plug at 9,400'

25 sx plug at 6,500'

Perforate squeeze holes at 4900' and pump 35sx plug

35 sx plug at 1,900'

25 sx plug at 60'

perforate holes @ 385' and squeeze 50' cut in 50' cut back.

We will then install a dry hole marker and clear the location of all production equipment and junk pursuant to NMOC regulations.

12.5 lb gelled lime mud between plugs. CWD

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE President

DATE 12/4/02

Type or print name Phelps White

Telephone No. 505.622.1001

(This space for State use)

APPROVED BY

Chris Williams

TITLE

DISTRICT SUPERVISOR/GENERAL MANAGER

DATE DEC 09 2002

Conditions of approval, if any:

THE COMMISSION MUST BE NOTIFIED 24 HOURS PRIOR TO THE BEGINNING OF PLUGGING OPERATIONS FOR THE C-103 TO BE A