State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

Submit 3 Copies to Appropriate
District Office DISTRICT I P.O. Box 1980, Hobbs, NM 88240 DISTRICT II

OIL CONSERVATION DIVISION

WELL API NO. P.O. Box 2088 30-025-27891 5. Indicate Type of Lease

Santa Fe, New Mexico 87504-2088 P.O. Drawer DD. Artesia, NM 88210 FEE XX STATE 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. None SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Type of Well: Tilley 758 WELL X OTHER WELL. Name of Operator 8. Well No. Kennedy & Mitchell, Inc. 3. Address of Operator 9. Pool name or Wildcat 500 N. Loraine Suite 1050 Midland, TX Shoebar Devonian 4. Well Location 330 South 1815 Unit Letter . Feet From The Line and Feet From The Line 26 Lea Range **NMPM** Township County Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3965' GL Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON ALTERING CASING REMEDIAL WORK **TEMPORARILY ABANDON CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ARANDONMENT PULL OR ALTER CASING CASING TEST AND CEMENT JOB OTHER: OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed Rigged up Mayo Marrs Well Service on 2/21/92. Pulled & LD rods. Poh w/ tbg. PU tbg. TIH w/ tubing. 2/24/92- Fin TIH w/ tbg to 8455'. SDON. 2/25/92-PU 2-7/8" tbg & fin TIH to 12423'. Pump 25 sx cmt. Toh w/ tbg to 9923' & WOC. TIH w/ tbg & tag plug @ 12303'. POH w/ tbg to 9500'. Girc hole w/ 10ppg salt gel mud. Pump 25 sx cmt (265' plug). POH w/ tbg to 6500'.SDON. 2/26/92- pump 25 sx cmt (265' plug). POH w/ tbg. GIH w/ charge to 4714' & shoot csg. POH & LD 5-1/2" csg. SDON. 2/27/92- Fin LD 5-1/2" csg. TIH w/ tbg to 4764'. Pump 50 sx cmt. POH w/ tbg to 400'. RU wireline & TIH to tag plug. Tag plug @ 4556'. RD wireline. Pump 30 sx cmt @ 400' (116' plug). LD tbg. SDON. 2/28/92- Spot 10 sx cmt @ surface. Cut off wellhead. Erect permanent marker. RD Mayo Marrs Well Service. P & A complete 2/28/92. Tubulars left in wellbore: 13-3/8" 40# from surface to 378' (cemented to surface) 8-5/8" 24# & 32# from surface to 4851' (cemented to surface) 5-1/2" 17# & 20# from 4714' to 12508' (plug set @ top of stub) Open hole from 12508'-12558' (plug set @ 12303'-12423') I hereby certify that the information above is true and complete to the best of my knowledge and belief. Production Superintendent DATE 3-6-92 SIGNATURE = Jim McAninch TYPE OR PRINT NAME (915) 684-7732 (This space for State Use) OIL & GAS Limited On

CONDITIONS OF APPROVAL, IF ANY: