

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>		<p>5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/></p> <p>5. State Oil & Gas Lease No.</p>
<p>1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/></p>		<p>7. Unit Agreement Name</p>
<p>2. Name of Operator Great Western Drilling Company</p>		<p>8. Farm or Lease Name Glenn Cleveland</p>
<p>3. Address of Operator P.O. Box 1659, Midland, TX 79702</p>		<p>9. Well No. 1</p>
<p>4. Location of Well UNIT LETTER 0 , 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 7 TOWNSHIP 15-S RANGE 35-E NMPM.</p>		<p>10. Field and Pool, or Wildcat Wildcat</p>
<p>15. Elevation (Show whether DF, RT, GR, etc.) GL 4033.6'</p>		<p>12. County Lea</p>

<p align="center">16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data</p>			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-10-82: Spudded 17½" hole @ 8:15 a.m. T.D. Surface hole at 450' @ 8:15 p.m., 9-10-82. Ran 12 jts. 13 3/8", 48#/ft., H-40, ST & C, R-3, Casing and set at 450' KBM. Cemented with 455 Sxs. Class "C" cement plus 4% calcium chloride, mixed @ 14.8#/gal. Plug down @ 2:30 a.m., 9-11-82, circulated 100 Sxs.

9-11-82: WOC 12 hrs. Nipped up and tested BOP & 13 3/8" Csg. to 1,000 psi for 30 min.-held.

9-12-82: Drilling ahead @ 1,750'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *M. H. Whelan* TITLE Asst. to Gen. Supt. DATE 9-15-82

APPROVED BY JERRY SEXTON TITLE DISTRICT 1 SUPR. DATE SEP 20 1982