

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator TEXACO Inc.	8. Farm or Lease Name Lee Carter
3. Address of Operator P. O. Box 728, Hobbs, New Mexico 88240	9. Well No. 1
4. Location of Well UNIT LETTER H 1980 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 33 TOWNSHIP 16-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Casey Strawn
15. Elevation (Show whether DF, RT, GR, etc.) 3778' (GR)	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Perforate & Treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TOTAL DEPTH 11,515'
PLUG BACK TOTAL DEPTH 11,455'
13 3/8" OD 48# H-40 CSG SET @ 377'
8 5/8" OD 24# & 32# S-80 & K-55 CSG SET @ 4800'.
5 1/2" OD 17# S-95, N-80 & K-55 CSG SET @ 11,515'.

1. Perforated 5 1/2" OD Csg W/2-JSPF from 11,220'-11,224', 11,232,-11,245', 11,262-11,268, & 11,285-11,289'.
2. Set pkr. @ 11,071' Acidize perfs 11,220'-11,289' W/2500 gals. 15% NE Acid.
3. Perforate 5 1/2" Csg W/4-JSPF @ same intervals as shown above.
4. Set pkr. @ 11,160' Acidize perfs. 11,220'-11,289' W/2500 gals. 15% NE Acid.
5. Swab Well.
6. Reset pkr. @ 11,163'.
7. Acidize perfs. 11,220'-11,289' W/8000 gals. 15% NE Acid in 2-stages W/100# rock salt between stages.
8. Install pumping equipment. On 24 hr. Potential Test ending 1-25-83, Well pumped 43 BO & 16 BW, GOR 593.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie Seay TITLE Asst. Dist. Mgr. DATE 1-27-83

ORIGINAL SIGNED BY EDDIE SEAY

APPROVED BY OIL & GAS INSPECTOR TITLE _____ DATE JAN 31 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
JAN 28 1983
O.C.D.
HOBBS OFFICE