

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. This form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	2084	T. Canyon	10,946	T. Ojo Alamo	T. Penn. "B"
T. Salt	2146	T. Strawn	11,208	T. Kirtland-Fruitland	T. Penn. "C"
T. Salt	2989	T. Atoka		T. Pictured Cliffs	T. Penn. "D"
T. Yates	3102	T. Miss		T. Cliff House	T. Leadville
T. 7 Rivers	3372	T. Devonian		T. Menefee	T. Madison
T. Queen	3991	T. Silurian		T. Point Lookout	T. Elbert
T. Grayburg	4438	T. Montoya		T. Mancos	T. McCracken
T. San Andres	4745	T. Simpson		T. Gallup	T. Ignacio Qtzite
T. Glorieta	6130	T. McKee		Base Greenhorn	T. Granite
T. Paddock	6220	T. Ellenburger		T. Dakota	
T. Blinberry		T. Gr. Wash		T. Morrison	
T. Tubb	7627	T. Granite		T. Todilto	
T. Drinkard	7780	T. Delaware Sand		T. Entrada	
T. Abo	8055	T. Bone Springs		T. Wingate	
T. Wolfcamp	10,097			T. Chinle	
T. Penn.	10,818			T. Pennian	
T. Cisco (Bough C)				T. Penn. "A"	

OIL OR GAS SANDS OR ZONES

No. 1, from	to	No. 4, from	to
No. 2, from	to	No. 5, from	to
No. 3, from	to	No. 6, from	to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from	to	feet
No. 2, from	to	feet
No. 3, from	to	feet
No. 4, from	to	feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	377	377	Red Bed	9082	9278	196	Shale
377	3155	2778	Anhydrite	9278	10248	970	Lime & Shale
3155	3896	741	Anhydrite & dolomite	10248	11515	1267	Lime
3896	4123	227	Anhydrite & Lime				
4123	4158	35	Anhydrite			11515	TOTAL DEPTH
4158	6490	2332	Lime			11455	PSD
6490	7442	952	Dolomite				
7442	7771	329	Dolomite & Shale				
7771	8325	554	Dolomite & Lime				
8325	9082	757	Dolomite & Shale				

RECEIVED
FEB 10 1983
C. D.
HOBBS OFFICE