

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico				Northwestern New Mexico			
Rustler	1592	T. Canyon	10412	T. Ojo Alamo		T. Penn. "B"	
T. Anhy	2680	T. Strawn		T. Kirtland-Fruitland		T. Penn. "C"	
T. Salt Base		T. Atoka		T. Pictured Cliffs		T. Penn. "D"	
T. Salt		T. Miss		T. Cliff House		T. Leadville	
T. Yates	2760	T. Devonian		T. Menefee		T. Madison	
T. 7 Rivers		T. Silurian		T. Point Lookout		T. Elbert	
T. Queen	3580	T. Montoya		T. Mancos		T. McCracken	
T. Grayburg		T. Simpson		T. Gallup		T. Ignacio Qtzte	
T. San Andres	4256	T. McKee		Base Greenhorn		T. Granite	
T. Glorieta	5893	T. Ellenburger		T. Dakota		T.	
T. Paddock		T. Gr. Wash		T. Morrison		T.	
T. Blinberry		T. Granite		T. Todilto		T.	
T. Tubb	7191	T. Delaware Sand		T. Entrada		T.	
T. Drinkard		T. Bone Springs		T. Wingate		T.	
T. Abo	7938	T. XX Marker	9622	T. Chinle		T.	
T. Wolfcamp	9388	T. Virgilian	9976	T. Permian		T.	
T. Penn.		T.		T. Penn. "A"		T.	
T. Cisco (Bough C)		T.					

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....
 No. 2, from.....to..... No. 5, from.....to.....
 No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....
 No. 4, from.....to.....feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	84	84	Surface Rock	7630	7780	150	Dolomite
84	445	361	Redbeds, Surface	7780	8320	540	Dolomite, Anhydrite, Shale
445	1999	1554	Redbeds, Anhydrite	8320	9500	1180	Dolomite, Shale
1999	2499	500	Redbeds, Salt, Anhy.	9500	10480	980	LS, Dolomite, Shale
2499	2785	286	Salt, Anhydrite				
2785	4666	1881	Anhydrite, Dolomite				
4666	4900	234	Dolomite, Shale				
4900	5200	300	Dolomite, Lime, Shale				
5200	5240	40	Limestone, Dolomite				
5240	5400	160	Dolomite, Lime, Shale				
5400	5560	160	Dolomite, Limestone				
5560	5800	240	Dolomite, Limestone, Cher				
5800	6100	300	Dolomite, Anhydrite				
6100	6320	220	Dolomite, Anhydrite, Sd.				
6320	6540	220	Anhydrite, Dolomite				
6540	7130	590	Dolomite				
7130	7630	500	Dolomite, Sand, Shale				