STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

DISTRIBUTION		
BANTAFE		
FILE		
U.S.G.S.	Ī	<u> </u>
LAND OFFICE		
OPERATOR	1	

	1 0 0	CONSERVA	HOM DIV	1510N		
DISTRIBUTION		P. O. BO)	< 2088			Form C-10] Revised 19-1-78
SANTA FE	SAN	TA FE, NEW	MEXICO 83	7501		WC41360 13-1-70
FILE	_				Sa. Indicate Typ	e of Leuse
U.\$.0.\$.	_				State X	Fon
LAND OFFICE	_				5. State Cir. & G	us Legge No.
OPERATOR	لـ				LG 706	
					mm	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
SUND	RY NOTICES AND	REPORTS ON	WELLS ACR TO A DIFFERE A PROPOSACE.	NT RESTRYOIR.		
614 X					7. Unit Agreeme	nt Manie
WELL A WELL OTHER-					8. Farm or Leus	e Name
Name of Operator					1	
Yates Petroleum Corporation				Vulture VP State		
Address of Operator				9. Well No.	•	
207 South 4th St., Artesia, NM 88210					<u> </u>	
Location of Well				10. Field and P		
UNIT LETTER D	330	North	LINE AND	330 **** ***	, sambesi	Birin 18 by
UNIT CETTER		1 186				
West LINE, SECT	14	15S		33E	VIIIIIII	
THELINE, SECT	10H T	OWNSHIP	RANGE	NMPM	Allllli	
mmmm.	TTTT 15 Flova	tion (Show whether	DF, RT, GR, etc	.)	12. County	7777777
		4178' GR			Lea	
711111111111111111111111111111111111111	777777					
°. Check	Appropriate Box	To Indicate N	ature of Not			
NOTICE OF 1	INTENTION TO:			SUBSEQUEN	T REPORT OF	:
			!			
-CRFORM REMEDIAL WORK	PLUG	AND ABANDON	REMEDIAL WORK		ALTE	RING CASING
EMPORARILY ASANDON			COMMENCE DRIL	LING OPHS.	PLUG	AND ABANDONMENT
-ULL OR ALTER CABING	CHA	IGE PLANS	CASING TEST AN	D CEMENT JOB X		
-yet on attention the						
OTHER						
7, Describe Proposed or Completed C	Operations (Clearly sta	te all pertinent deta	ils, and give per	tinent dates, includin	g estimated date of	starting any proposed
work) SEE RULE 1103.						

TD 445'. Moved out Cable Tool rig and moved in Rotary rig and continued drilling 11-22-82. Reamed hole to 17-1/2" 10:00 PM 11-22-82. Ran 11 jts of 13-3/8" 48# casing set at 445'. 1-Texas Pattern notched guide shoe set at 445'. Insert float at 403'. Cemented w/450 sx Class "C" 2% CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 9:00 AM 11-23-82. Bumped plug to 650 psi, released pressure, held okay, WOC. Drilled out 9:00 PM 11-23-82. WOC 12 hours. Cut off and welded on flow nipple. Reduced hole to 12-1/4". Drilled plug and resumed drilling.

1. ante Doodlest	e to the best of my knowledge and belief.	DATE 12-3-82
ORIGINAL SIGNED BY	TITLE	DEC 7 1982